



# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

Issue date: 10/10/2024 Revision date: 29/11/2022 Supersedes version of: 29/4/2010 Version: 1.8

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : FARECLA G3 PRO RESIN SUPERWAX  
Product code : FA7166

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Consumer use  
Use of the substance/mixture : Polishes and wax blends.

##### 1.2.2. Uses advised against

Restrictions on use : This material should not be used for any other purpose than the identified uses without expert advice. Improper use may cause potential health, safety and environmental risks.

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Farecla Products Limited  
Broadmeads  
Ware, SG12 9HS – Hertfordshire  
UK  
T +44 (0)19 2046 5041 (8:30-16:30 Monday to Friday)  
F +44 (0)19 2046 6557  
[technical@farecla.com](mailto:technical@farecla.com) - [www.farecla.com](http://www.farecla.com)

##### Supplier

Wyatt Machine Tools (Rupes) NZ Limited  
388 Church Street  
Penrose  
Auckland  
New Zealand  
T (09) 525 1000, F (09) 525 1009

#### 1.4. Emergency telephone number

Emergency number : 0800 992 881 (0800WYATT1)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not Classified

##### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P102 - Keep out of reach of children.  
EUH-statements : EUH208 - Contains 1,2-benzisothiazol-3(2H)-one(2634-33-5), 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone(55965-84-9). May produce an allergic reaction.  
Child-resistant fastening : Not applicable  
Tactile warning : Not applicable

#### 2.3. Other hazards

Other hazards which do not result in classification : If in eyes: this material may cause mechanical irritation.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

Component	
1,2-benzisothiazol-3(2H)-one (2634-33-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Sodium Nitrate (7631-99-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-47-8 EC-No.: 926-141-6 REACH-no: 01-2119456620-43	10 – 30	Asp. Tox. 1, H304
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS-No.: 64742-48-9 EC-No.: 918-481-9 REACH-no: 01-2119457273-39	1 – 10	Asp. Tox. 1, H304
2-Aminoethanol	CAS-No.: 141-43-5 EC-No.: 205-483-3 EC Index-No.: 603-030-00-8 REACH-no: 01-2119486455-28	< 0.1	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Chronic 2, H411
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	< 0.05	Skin Sens. 1, H317 Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Irrit. 2, H315 Aquatic Acute 1, H400
Sodium Nitrate	CAS-No.: 7631-99-4 EC-No.: 231-554-3 REACH-no: 01-2119488221-41	< 0.003	Ox. Sol. 3, H272 Eye Irrit. 2, H319
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	CAS-No.: 55965-84-9 EC-No.: 911-418-6 EC Index-No.: 613-167-00-5 REACH-no: 01-2120764691-48	< 0.0015	Acute Tox. 3 (Oral), H301 Acute Tox. 2 (Dermal), H310 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

Specific concentration limits:		
Name	Product identifier	Specific concentration limits
2-Aminoethanol	CAS-No.: 141-43-5 EC-No.: 205-483-3 EC Index-No.: 603-030-00-8 REACH-no: 01-2119486455-28	( 5 ≤C < 100) STOT SE 3, H335
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	( 0.05 ≤C ≤ 100) Skin Sens. 1, H317
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	CAS-No.: 55965-84-9 EC-No.: 911-418-6 EC Index-No.: 613-167-00-5 REACH-no: 01-2120764691-48	( 0.0015 ≤C ≤ 100) Skin Sens. 1A, H317 ( 0.06 ≤C < 0.6) Skin Irrit. 2, H315 ( 0.06 ≤C < 0.6) Eye Irrit. 2, H319 ( 0.6 ≤C ≤ 100) Skin Corr. 1C, H314 ( 0.6 ≤C ≤ 100) Eye Dam. 1, H318

Comments : Contains amongst other ingredients:  
15-30% aliphatic hydrocarbons; 5-15% zeolites; <5% nonionic surfactants, polycarboxylates, perfume, colourant, chloromethylisothiazolinone, methylisothiazolinone, benzisothiazolinone. For more ingredient information visit [www.farecla.com](http://www.farecla.com)

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.  
First-aid measures after skin contact : Take off contaminated clothing. Wash skin with plenty of water. If skin irritation occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Rinse mouth out with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Contact during a long period may cause light irritation.  
Symptoms/effects after eye contact : May cause eye irritation. redness, itching, tears.  
Symptoms/effects after ingestion : May cause irritation to the digestive tract. Abdominal pain, nausea.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : None known.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Unidentified organic compounds may be formed in fumes and smoke during combustion.  
Reactivity in case of fire : Product is not explosive.  
Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon dioxide. Carbon monoxide. Nitrogen oxides.

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

### 5.3. Advice for firefighters

Precautionary measures fire	: Keep container closed when not in use.
Firefighting instructions	: Evacuate area. Exercise caution when fighting any chemical fire. Fight fire with normal precautions from a reasonable distance. In case of fire: stop leak if safe to do so.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: High temperature decomposition products are harmful by inhalation.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid contact with skin and eyes. Stop leak if safe to do so. Clean up any spills as soon as possible, using an absorbent material to collect it.
------------------	---

#### 6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Keep upwind. Evacuate area.

#### 6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so. Cover spill with non combustible material, e.g.: sand/earth.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal. Clean contaminated surfaces with an excess of water.
Other information	: Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep cool. Keep at temperatures above freezing. Allowing freezing conditions may degrade product. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Incompatible products	: Strong acids. Oxidizing agent.
Incompatible materials	: Oxidizers (strong).
Information on mixed storage	: Store away from foodstuffs.
Storage area	: Store away from heat. Store in a well-ventilated place.

### 7.3. Specific end use(s)

Refer to Section 1.2 - Relevant identified uses.

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### 8.1.1 National occupational exposure and biological limit values

#### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

##### Switzerland - Occupational Exposure Limits

Local name	Distillats légers de pétrole, hydrotraités (vapeurs) / Destillate (Erdöl), mit Wasserstoff behandelte, leichte (Dampf)
MAK (OEL TWA) [1]	350 mg/m <sup>3</sup>
MAK (OEL TWA) [2]	50 ppm (vapour)
KZGW (OEL STEL)	700 mg/m <sup>3</sup>
KZGW (OEL STEL) [ppm]	100 ppm (vapour)
Critical toxicity	SNC / ZNS
Notation	SS <sub>C</sub> / SS <sub>C</sub>
Remark	OSHA
Regulatory reference	www.suva.ch, 28.03.2022

#### 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

##### Austria - Occupational Exposure Limits

MAK (OEL TWA)	0.05 mg/m <sup>3</sup> (5-Chloro-2-methyl-2,3-dihydroisothiazol-3-one and 2-methyl-2,3-dihydroisothiazol-3-one mixture in ratio 3:1)
OEL chemical category	Skin sensitizer

##### Switzerland - Occupational Exposure Limits

Local name	2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle et 2,3-dihydro-isothiazol-3-one de 2-méthyle [2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle, 2,3-Dihydro-isothiazol-3-one de 2-méthyle] / 5-Chlor-2-methyl-2,3-dihydro-isothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on [2-Methyl-2,3-dihydroisothiazol-3-on, 5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on]
MAK (OEL TWA) [1]	0.2 mg/m <sup>3</sup> (i) / (e)
KZGW (OEL STEL)	0.4 mg/m <sup>3</sup> (i) / (e)
Critical toxicity	VRS, Peau, Yeux / OAW, Haut, Auge
Notation	S, SS <sub>C</sub> / S, SS <sub>C</sub>
Regulatory reference	www.suva.ch, 28.03.2022

#### Sodium Nitrate (7631-99-4)

##### Czech Republic - Occupational Exposure Limits

PEL (OEL TWA)	6 mg/m <sup>3</sup> (dust)
---------------	----------------------------

#### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)

##### Poland - Occupational Exposure Limits

Local name	Benzyna do lakierów
NDS (OEL TWA)	300 mg/m <sup>3</sup>
NDSCh (OEL STEL)	900 mg/m <sup>3</sup>
Regulatory reference	Dz. U. 2018 poz. 1286

##### Switzerland - Occupational Exposure Limits

Local name	Naphta lourde (pétrole), hydrotraité / Naphtha (Erdöl), mit Wasserstoff behandelte, schwere
------------	---

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)	
MAK (OEL TWA) [1]	300 mg/m <sup>3</sup>
MAK (OEL TWA) [2]	50 ppm
KZGW (OEL STEL)	600 mg/m <sup>3</sup>
KZGW (OEL STEL) [ppm]	100 ppm
Critical toxicity	SNC / ZNS
Regulatory reference	www.suva.ch, 28.03.2022
2-Aminoethanol (141-43-5)	
EU - Indicative Occupational Exposure Limit (IOEL)	
IOEL TWA	2.5 mg/m <sup>3</sup>
IOEL TWA [ppm]	1 ppm
IOEL STEL	7.6 mg/m <sup>3</sup>
IOEL STEL [ppm]	3 ppm
Remark	Possibility of significant uptake through the skin
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	2.5 mg/m <sup>3</sup>
MAK (OEL TWA) [ppm]	1 ppm
MAK (OEL STEL)	7.6 mg/m <sup>3</sup>
MAK (OEL STEL) [ppm]	3 ppm
OEL chemical category	Skin sensitizer
Belgium - Occupational Exposure Limits	
Local name	Ethanolamine # Ethanolamine
OEL TWA	2.5 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m <sup>3</sup>
OEL STEL [ppm]	3 ppm
Remark	D: la mention "D" signifie que la r�sorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette r�sorption peut se faire tant par contact direct que par pr�sence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.
OEL chemical category	Skin, Skin notation
Regulatory reference	Koninklijk besluit/Arr�t� royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Етаноламин (2-Аминоетанол)
OEL TWA	2.5 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m <sup>3</sup>
OEL STEL [ppm]	3 ppm
Remark	Кожа (възможна е значителна резорбция чрез кожата); • (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

<b>2-Aminoethanol (141-43-5)</b>	
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
<b>Croatia - Occupational Exposure Limits</b>	
GVI (OEL TWA) [1]	2.5 mg/m <sup>3</sup>
GVI (OEL TWA) [2]	1 ppm
KGVI (OEL STEL)	7.6 mg/m <sup>3</sup>
KGVI (OEL STEL) [ppm]	3 ppm
OEL chemical category	Skin notation
<b>Cyprus - Occupational Exposure Limits</b>	
OEL TWA	2.5 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m <sup>3</sup>
OEL STEL [ppm]	3 ppm
OEL chemical category	Skin-potential for cutaneous absorption
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	2-Aminoethanol (Ethanolamin)
PEL (OEL TWA)	2.5 mg/m <sup>3</sup>
PEL (OEL TWA) [ppm]	1 ppm
NPK-P (OEL C)	7.5 mg/m <sup>3</sup>
NPK-P (OEL C) [ppm]	3 ppm
Remark	I - dráždí sliznice (oči, dýchací cesty), respektive kůži.
OEL chemical category	Potential for cutaneous absorption
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
<b>Denmark - Occupational Exposure Limits</b>	
OEL TWA [1]	2.5 mg/m <sup>3</sup>
OEL TWA [2]	1 ppm
OEL chemical category	Potential for cutaneous absorption
<b>Estonia - Occupational Exposure Limits</b>	
OEL TWA	2.5 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m <sup>3</sup>
OEL STEL [ppm]	3 ppm
OEL chemical category	Skin notation
<b>Finland - Occupational Exposure Limits</b>	
Local name	2-Aminoetanoli
HTP (OEL TWA) [1]	2.5 mg/m <sup>3</sup>
HTP (OEL TWA) [2]	1 ppm
HTP (OEL STEL)	7.6 mg/m <sup>3</sup>
HTP (OEL STEL) [ppm]	3 ppm
Remark	Iho

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

<b>2-Aminoethanol (141-43-5)</b>	
OEL chemical category	Potential for cutaneous absorption
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystministeriö)
<b>France - Occupational Exposure Limits</b>	
Local name	Ethanolamine (2-Aminoéthanol)
VME (OEL TWA)	2.5 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	1 ppm
VLE (OEL C/STEL)	7.6 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	3 ppm
Remark	Valeurs réglementaires contraignantes; risque de pénétration percutanée
OEL chemical category	Risk of cutaneous absorption
Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487; Décret n° 2020-1546; Décret n° 2021-434; Décret n° 2021-1849)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
Local name	2-Amino-ethanol
AGW (OEL TWA) [1]	0.5 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	0.2 ppm
Peak exposure limitation factor	1(l)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); EU - Europäische Union (Von der EU wurde ein Luftgrenzwert festgelegt: Abweichungen bei Wert und Spitzenbegrenzung sind möglich); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden; Sh - Hautsensibilisierender Stoff; H - hautresorptiv; 11 - Summe aus Dampf und Aerosolen
Chemical category	Skin notation, Skin sensitization
Regulatory reference	TRGS900
<b>Gibraltar - Occupational Exposure Limits</b>	
OEL TWA	2.5 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m <sup>3</sup>
OEL STEL [ppm]	3 ppm
OEL chemical category	Skin notation
<b>Greece - Occupational Exposure Limits</b>	
Local name	Αιθανολαμίνη (2-αμινοαιθανόλη)
OEL TWA	2.5 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m <sup>3</sup>
OEL STEL [ppm]	3 ppm
OEL chemical category	skin - potential for cutaneous absorption
Remark	Η ένδειξη «δέρμα» στις οριακές τιμές επαγγελματικής έκθεσης επισημαίνει το ενδεχόμενο σημαντικής διείσδυσης μέσω του δέρματος.
Regulatory reference	Π.Δ. 162/2007 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους



# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

<b>2-Aminoethanol (141-43-5)</b>	
<b>Hungary - Occupational Exposure Limits</b>	
AK (OEL TWA)	2.5 mg/m <sup>3</sup>
CK (OEL STEL)	7.6 mg/m <sup>3</sup>
OEL chemical category	Potential for cutaneous absorption
<b>Ireland - Occupational Exposure Limits</b>	
Local name	2-Aminoethanol [Ethanolamine]
OEL TWA [1]	2.5 mg/m <sup>3</sup>
OEL TWA [2]	1 ppm
OEL STEL	7.6 mg/m <sup>3</sup>
OEL STEL [ppm]	3 ppm
Remark	Sk (Substances which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body), IOELV (Indicative Occupational Exposure Limit Values)
OEL chemical category	Potential for cutaneous absorption
Regulatory reference	Chemical Agents Code of Practice 2021
<b>Italy - Occupational Exposure Limits</b>	
Local name	2-Amminoetanolo
OEL TWA	2.5 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m <sup>3</sup>
OEL STEL [ppm]	3 ppm
Remark	Cute
OEL chemical category	skin - potential for cutaneous absorption
Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
<b>Latvia - Occupational Exposure Limits</b>	
OEL TWA	0.5 mg/m <sup>3</sup>
OEL TWA [ppm]	0.2 ppm
OEL chemical category	skin - potential for cutaneous exposure
<b>Lithuania - Occupational Exposure Limits</b>	
IPRV (OEL TWA)	2.5 mg/m <sup>3</sup>
IPRV (OEL TWA) [ppm]	1 ppm
TPRV (OEL STEL)	7.6 mg/m <sup>3</sup>
TPRV (OEL STEL) [ppm]	3 ppm
OEL chemical category	Skin notation
<b>Luxembourg - Occupational Exposure Limits</b>	
OEL TWA	2.5 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m <sup>3</sup>
OEL STEL [ppm]	3 ppm
OEL chemical category	Possibility of significant uptake through the skin

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

2-Aminoethanol (141-43-5)	
<b>Malta - Occupational Exposure Limits</b>	
OEL TWA	2.5 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m <sup>3</sup>
OEL STEL [ppm]	3 ppm
OEL chemical category	Possibility of significant uptake through the skin
<b>Netherlands - Occupational Exposure Limits</b>	
Local name	2-Aminoethanol
TGG-8u (OEL TWA)	2.5 mg/m <sup>3</sup>
TGG-15min (OEL STEL)	7.6 mg/m <sup>3</sup>
Remark	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
MAC chemical category	Skin notation
Regulatory reference	Arbeidsomstandighedenregeling 2022
<b>Poland - Occupational Exposure Limits</b>	
Local name	2-Aminoetanol
NDS (OEL TWA)	2.5 mg/m <sup>3</sup>
NDSch (OEL STEL)	7.5 mg/m <sup>3</sup>
Remark	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową).
Regulatory reference	Dz. U. 2018 poz. 1286
<b>Portugal - Occupational Exposure Limits</b>	
OEL TWA	2.5 mg/m <sup>3</sup> (indicative limit value)
OEL TWA [ppm]	1 ppm (indicative limit value)
OEL STEL	7.6 mg/m <sup>3</sup> (indicative limit value)
OEL STEL [ppm]	3 ppm (indicative limit value)
OEL chemical category	skin - potential for cutaneous exposure indicative limit value
<b>Romania - Occupational Exposure Limits</b>	
OEL TWA	2.5 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m <sup>3</sup>
OEL STEL [ppm]	3 ppm
OEL chemical category	Skin notation
<b>Slovakia - Occupational Exposure Limits</b>	
NPHV (OEL TWA) [1]	2.5 mg/m <sup>3</sup>
NPHV (OEL TWA) [2]	1 ppm
NPHV (OEL C)	7.6 mg/m <sup>3</sup>
OEL chemical category	Potential for cutaneous absorption

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

2-Aminoethanol (141-43-5)	
<b>Slovenia - Occupational Exposure Limits</b>	
OEL TWA	2.5 mg/m <sup>3</sup>
OEL TWA [ppm]	1 ppm
OEL STEL	7.6 mg/m <sup>3</sup>
OEL STEL [ppm]	3 ppm
OEL chemical category	Potential for cutaneous absorption
<b>Spain - Occupational Exposure Limits</b>	
Local name	2-Aminoetanol (Etanolamina)
VLA-ED (OEL TWA) [1]	2.5 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	1 ppm
VLA-EC (OEL STEL)	7.5 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	3 ppm
Remark	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo).
OEL chemical category	skin - potential for cutaneous absorption
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
<b>Sweden - Occupational Exposure Limits</b>	
Local name	Etanolamin
NGV (OEL TWA)	2.5 mg/m <sup>3</sup>
NGV (OEL TWA) [ppm]	1 ppm
KTV (OEL STEL)	7.5 mg/m <sup>3</sup>
KTV (OEL STEL) [ppm]	3 ppm
Remark	H (Ämnet kan lätt upptas genom huden. Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga)
OEL chemical category	Skin notation
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
<b>United Kingdom - Occupational Exposure Limits</b>	
Local name	2-Aminoethanol
WEL TWA (OEL TWA) [1]	2.5 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	1 ppm
WEL STEL (OEL STEL)	7.6 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	3 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
WEL chemical category	Potential for cutaneous absorption
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
<b>Norway - Occupational Exposure Limits</b>	
Local name	2-aminoetanol (Etanolamin)
Grenseverdi (OEL TWA) [1]	2.5 mg/m <sup>3</sup>

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

2-Aminoethanol (141-43-5)	
Grønseverdi (OEL TWA) [2]	1 ppm
Korttidsverdi (OEL STEL)	5 mg/m <sup>3</sup> (value calculated)
Korttidsverdi (OEL STEL) [ppm]	2 ppm (value calculated)
Remark	H: Kjemikalier som kan tas opp gjennom huden; E: EU har en veiledende grøenseverdi og/eller anmerkning for stoffet.
OEL chemical category	Skin notation
Regulatory reference	FOR-2021-06-28-2248
Switzerland - Occupational Exposure Limits	
Local name	2-Aminoéthanol / 2-Aminoethanol [Ethanolamin]
MAK (OEL TWA) [1]	5 mg/m <sup>3</sup>
MAK (OEL TWA) [2]	2 ppm
KZGW (OEL STEL)	10 mg/m <sup>3</sup>
KZGW (OEL STEL) [ppm]	4 ppm
Critical toxicity	Peau, Fatigue, Yeux / Haut, Fatigue, Auge
Notation	S / S
Remark	NIOSH
OEL chemical category	Sensitizer
Regulatory reference	www.suva.ch, 28.03.2022
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethanolamine
ACGIH OEL TWA [ppm]	3 ppm
ACGIH OEL STEL [ppm]	6 ppm
Remark (ACGIH)	TLV® Basis: Eye & skin irr
Regulatory reference	ACGIH 2022

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

Personal protective equipment symbol(s):



### 8.2.2.1. Eye and face protection

**Eye protection:**

Chemical goggles or safety glasses

### 8.2.2.2. Skin protection

**Skin and body protection:**

Wear suitable protective clothing

**Hand protection:**

Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl").

### 8.2.2.3. Respiratory protection

**Respiratory protection:**

No respiratory protection needed under normal use conditions. If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable.

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

**Environmental exposure controls:**

Avoid release to the environment.

**Consumer exposure controls:**

The substance is not classified for human health hazards or for environment effects and it is not PBT or vPvB so that no exposure assessment or risk characterisation is required. For tasks where the intervention of workers is required, the substance must be handled in accordance with good industrial hygiene and safety procedures.

**Other information:**

Do not eat, drink or smoke when using this product. Provide readily accessible eye wash stations and safety showers.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Purple.
Odour	: pleasant.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Explosive properties	: Product is not explosive.
Oxidising properties	: Non oxidizing material according to EC criteria.
Explosive limits	: Not available
Lower explosion limit	: Not applicable.
Upper explosion limit	: Not applicable.
Flash point	: > 93 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 7.5 – 8.5
Viscosity, kinematic	: 10000 mm <sup>2</sup> /s 20°C
Viscosity, dynamic	: 6500 – 12000 cP Brookfield viscometer
Solubility	: Slightly soluble.
Partition coefficient n-octanol/water (Log Kow)	: Not available

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 0.98 – 1
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

VOC content : 167 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Strong oxidizers. Strong acids.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not Classified
Acute toxicity (dermal)	: Not Classified
Acute toxicity (inhalation)	: Not Classified

#### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h

#### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

LD50 oral rat	490 mg/kg bodyweight
LD50 oral	670 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight
LD50 dermal	4115 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	100 mg/l

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

### 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

LD50 oral rat	66 mg/kg bodyweight
LD50 dermal rat	> 1008 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	0.17 mg/l air

### Sodium Nitrate (7631-99-4)

LD50 oral rat	≈ 3430 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	3700 mg/kg
LD50 dermal rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

### 2-Aminoethanol (141-43-5)

LD50 oral rat	1089 mg/kg Source: OECD SIDS
LD50 dermal rabbit	2504 mg/kg Source: OECD SIDS
LD50 dermal	1018 mg/kg
LC50 Inhalation - Rat (Vapours)	> 1487 mg/l Source: ECHA

Skin corrosion/irritation : Not Classified  
pH: 7.5 – 8.5

### 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

pH	3.43 Temp.: 20 °C Concentration: 10 g/L
----	---

### Sodium Nitrate (7631-99-4)

pH	7 Temp.: 25 °C Remarks on result: 'other:'
----	--

### 2-Aminoethanol (141-43-5)

pH	≈ 12
----	------

Serious eye damage/irritation : Not Classified  
pH: 7.5 – 8.5

### 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

pH	3.43 Temp.: 20 °C Concentration: 10 g/L
----	---

### Sodium Nitrate (7631-99-4)

pH	7 Temp.: 25 °C Remarks on result: 'other:'
----	--

### 2-Aminoethanol (141-43-5)

pH	≈ 12
----	------

Respiratory or skin sensitisation : Not Classified  
Germ cell mutagenicity : Not Classified  
Carcinogenicity : Not Classified  
Reproductive toxicity : Not Classified

### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

NOAEL (animal/female, F1)	56.6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
---------------------------	---

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

STOT-single exposure : Not Classified

### 2-Aminoethanol (141-43-5)

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not Classified

### 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

LOAEL (dermal, rat/rabbit, 90 days) : 0.525 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)

### Sodium Nitrate (7631-99-4)

NOAEL (oral, rat, 90 days) : ≥ 1500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

### 2-Aminoethanol (141-43-5)

NOAEL (oral, rat, 90 days) : 300 mg/kg bodyweight Animal: rat, Guideline: other:OECD Guideline 416 (Two-generation reproduction toxicity study)

Aspiration hazard : Not Classified

### FARECLA G3 PRO RESIN SUPERWAX

Viscosity, kinematic : 10000 mm<sup>2</sup>/s 20°C

### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

Hydrocarbon : Yes

### Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-48-9)

Viscosity, kinematic : 1.8 mm<sup>2</sup>/s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm<sup>2</sup>/s)'

### 2-Aminoethanol (141-43-5)

Viscosity, kinematic : 18.578 mm<sup>2</sup>/s

## 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not Classified

Hazardous to the aquatic environment, long-term (chronic) : Not Classified

Not rapidly degradable

### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

LC50 - Fish [1] : 2.2 mg/l

### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

LC50 - Fish [1] : 2.18 mg/l

LC50 - Fish [2] : 2.15 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)

EC50 - Crustacea [1] : 2.94 mg/l

EC50 - Crustacea [2] : 2.9 mg/l Test organisms (species): Daphnia magna

EC50 - Other aquatic organisms [1] : 2.94 mg/l waterflea



# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
EC50 - Other aquatic organisms [2]	0.11 mg/l
ErC50 algae	150 µg/l
<b>5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)</b>	
LC50 - Fish [1]	0.19 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	0.28 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	0.16 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	0.0052 mg/l (Skeletonema costatum) (OECD 201)
EC50 72h - Algae [1]	0.048 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC (chronic)	0.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.098 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '28 d'
NOEC chronic crustacea	0.004 mg/l 21 d (Daphnia) (OECD 211)
NOEC chronic algae	0.0012 mg/l 72 h (Pseudokirchneriella subcapitata) (OECD 201)
<b>Sodium Nitrate (7631-99-4)</b>	
LC50 - Fish [1]	1559 mg/l Test organisms (species): other:
LC50 - Fish [2]	1354 mg/l Test organisms (species): other:
EC50 - Crustacea [1]	8609 mg/l
<b>2-Aminoethanol (141-43-5)</b>	
LC50 - Fish [1]	170 mg/l Source: OECD SIDS
LC50 - Fish [2]	3684 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 - Crustacea [1]	32.6 mg/l
EC50 72h - Algae [1]	2.8 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	2.1 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	2.1 mg/l Source: ECHA
NOEC (chronic)	0.85 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	1.24 mg/l Test organisms (species): Oryzias latipes Duration: '41 d'

### 12.2. Persistence and degradability

<b>FARECLA G3 PRO RESIN SUPERWAX</b>	
Persistence and degradability	Readily biodegradable.
<b>Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics (64742-47-8)</b>	
Persistence and degradability	No persistence data available for this product.

### 12.3. Bioaccumulative potential

<b>FARECLA G3 PRO RESIN SUPERWAX</b>	
Bioaccumulative potential	No indication of bio-accumulation potential.
<b>Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics (64742-47-8)</b>	
Partition coefficient n-octanol/water (Log Kow)	6 – 8.2

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

BCF - Fish [1]	6.62
Partition coefficient n-octanol/water (Log Pow)	-0.9 – 0.99

### 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

BCF - Fish [1]	41 – 54
Bioconcentration factor (BCF REACH)	3.6 (calculated) S 1177
Partition coefficient n-octanol/water (Log Pow)	0.75

### Sodium Nitrate (7631-99-4)

Partition coefficient n-octanol/water (Log Pow)	-3.8
---	------

### 2-Aminoethanol (141-43-5)

Partition coefficient n-octanol/water (Log Pow)	-1.31 Source: ICSC
Partition coefficient n-octanol/water (Log Kow)	-1.31

## 12.4. Mobility in soil

### FARECLA G3 PRO RESIN SUPERWAX

Ecology - soil	Readily absorbed into soil.
----------------	-----------------------------

### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

Surface tension	72.6 mN/m
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.97

### 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.81 – 1
--	----------

## 12.5. Results of PBT and vPvB assessment

### FARECLA G3 PRO RESIN SUPERWAX

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

## 12.6. Endocrine disrupting properties

The mixture does not contain substances listed in accordance with Article 59(1) of the REACH Regulation as having endocrine disrupting properties according to the criteria described in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 in a concentration equal to or greater than 0,1 %.

## 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
European List of Waste (LoW) code : 08 04 12 - adhesive and sealant sludges other than those mentioned in 08 04 11

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.2. UN proper shipping name</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not regulated

#### Transport by sea

Not regulated

#### Air transport

Not regulated

#### Inland waterway transport

Not regulated

#### Rail transport

Not regulated

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. New Zealand Regulation

This mixture is not classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017.

#### 15.1.2. National regulations

Listed on ELINCS (European List of Notified Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on INSQ (Mexican National Inventory of Chemical Substances)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)  
Listed on the Canadian DSL (Domestic Substances List)  
Listed on the Japanese ENCS (Existing New Chemical Substances) inventory  
Listed on KECL/KECI (Korean Existing Chemicals Inventory)  
Listed on the TCSI (Taiwan Chemical Substance Inventory)  
Listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

### SECTION 16: Other information

#### Abbreviations and acronyms:

ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
IARC	International Agency for Research on Cancer
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
SDS	Safety Data Sheet
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
BLV	Biological limit value
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC50	Median effective concentration
EC-No.	European Community number
EN	European Standard
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OEL	Occupational Exposure Limit
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
vPvB	Very Persistent and Very Bioaccumulative
WGK	Water Hazard Class

#### Full text of H- and EUH-statements:

Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4

# FARECLA G3 PRO RESIN SUPERWAX

## Safety Data Sheet (New Zealand)

### Full text of H- and EUH-statements:

Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains 1,2-benzisothiazol-3(2H)-one(2634-33-5), 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone(55965-84-9). May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H272	May intensify fire; oxidiser.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Ox. Sol. 3	Oxidising Solids, Category 3
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Safety Data Sheet (SDS), EU

While Farecla Products Ltd. believes that the data and information contained herein are factual and the opinions are those of qualified experts, they are not to be taken as a warranty or representation for which Farecla assumes any legal responsibility. They are offered solely for the consideration, investigation, data and information in accordance with applicable laws and regulations.