



# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

Issue date: 10/10/2024 Revision date: 25/11/2022 Supersedes version of: 7/5/2012 Version: 1.6

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : FARECLA G3 PRO SCRATCH REMOVER LIQUID  
Product code : FA7164

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public  
Main use category : Consumer use  
Use of the substance/mixture : Abrasive polishing compound

##### 1.2.2. Uses advised against

Restrictions on use : This material should not be used for any other purpose than the identified uses without expert advice. Improper use may cause potential health, safety and environmental risks.

#### 1.3. Details of the supplier of the safety data sheet

##### Manufacturer

Farecla Products Limited  
Broadmeads  
Ware, SG12 9HS – Hertfordshire  
UK  
T +44 (0)19 2046 5041 (8:30-16:30 Monday to Friday)  
F +44 (0)19 2046 6557  
[technical@farecla.com](mailto:technical@farecla.com) - [www.farecla.com](http://www.farecla.com)

##### Supplier

Wyatt Machine Tools (Rupes) NZ Limited  
388 Church Street  
Penrose  
Auckland  
New Zealand  
T (09) 525 1000, F (09) 525 1009

#### 1.4. Emergency telephone number

Emergency number : 0800 992 881 (0800WYATT1)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not Classified

##### Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP) : P102 - Keep out of reach of children.  
EUH-statements : EUH208 - Contains 1,2-benzisothiazol-3(2H)-one(2634-33-5), 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone(55965-84-9). May produce an allergic reaction.  
Child-resistant fastening : Not applicable  
Tactile warning : Not applicable

#### 2.3. Other hazards

Other hazards which do not result in classification : If in eyes: this material may cause mechanical irritation.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

Contains no PBT/vPvB substances  $\geq 0.1\%$  assessed in accordance with REACH Annex XIII

Component	
Aluminium Oxide (1344-28-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Glycerine (56-81-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
White mineral oil (petroleum) (8042-47-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
1,2-benzisothiazol-3(2H)-one (2634-33-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Sodium Nitrate (7631-99-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Not applicable

#### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Aluminium Oxide	CAS-No.: 1344-28-1 EC-No.: 215-691-6 REACH-no: 01-2119529248-35	30 – 50	Not Classified
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-47-8 EC-No.: 926-141-6 REACH-no: 01-2119456620-43	10 – 30	Asp. Tox. 1, H304
Glycerine	CAS-No.: 56-81-5 EC-No.: 200-289-5 REACH-no: 01-2119471987-18	1 – 30	Not Classified
White mineral oil (petroleum)	CAS-No.: 8042-47-5 EC-No.: 232-455-8 REACH-no: 01-2119487078-27	1 – 30	Not Classified
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	< 0.05	Skin Sens. 1, H317 Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318 Skin Irrit. 2, H315 Aquatic Acute 1, H400

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Sodium Nitrate	CAS-No.: 7631-99-4 EC-No.: 231-554-3 REACH-no: 01-2119488221-41	< 0.003	Ox. Sol. 3, H272 Eye Irrit. 2, H319
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	CAS-No.: 55965-84-9 EC-No.: 911-418-6 EC Index-No.: 613-167-00-5 REACH-no: 01-2120764691-48	< 0.0015	Acute Tox. 3 (Oral), H301 Acute Tox. 2 (Dermal), H310 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	( 0.05 ≤C ≤ 100) Skin Sens. 1, H317
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	CAS-No.: 55965-84-9 EC-No.: 911-418-6 EC Index-No.: 613-167-00-5 REACH-no: 01-2120764691-48	( 0.0015 ≤C ≤ 100) Skin Sens. 1A, H317 ( 0.06 ≤C < 0.6) Skin Irrit. 2, H315 ( 0.06 ≤C < 0.6) Eye Irrit. 2, H319 ( 0.6 ≤C ≤ 100) Skin Corr. 1C, H314 ( 0.6 ≤C ≤ 100) Eye Dam. 1, H318

### Comments

: Contains amongst other ingredients:  
>30% zeolites; 5-15% aliphatic hydrocarbons; <5% nonionic surfactants, Methylchloroisothiazolinone, Methylisothiazolinone, Benzisothiazolinone. For more ingredient information visit [www.farecla.com](http://www.farecla.com)

Full text of H- and EUH-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Take off contaminated clothing. Wash skin with plenty of water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Prolonged or repeated contact may cause skin to become dry. Itching.
Symptoms/effects after eye contact	: May cause eye irritation. redness, itching, tears.
Symptoms/effects after ingestion	: Ingestion may cause nausea and vomiting.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.  
Unsuitable extinguishing media : None known.

#### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Unidentified organic compounds may be formed in fumes and smoke during combustion.  
Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon monoxide. Carbon dioxide. Nitrogen oxides.

#### 5.3. Advice for firefighters

Precautionary measures fire : Keep container closed when not in use.  
Firefighting instructions : Evacuate area. Exercise caution when fighting any chemical fire. Fight fire with normal precautions from a reasonable distance. In case of fire: stop leak if safe to do so.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.  
Other information : High temperature decomposition products are harmful by inhalation.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin and eyes. Stop leak if safe to do so. Clean up any spills as soon as possible, using an absorbent material to collect it.

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.  
Emergency procedures : Ventilate spillage area. Evacuate area. Keep upwind.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".  
Emergency procedures : Evacuate unnecessary personnel. Stop leak if safe to do so. Cover spill with non combustible material, e.g.: sand/earth.

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.  
Methods for cleaning up : Take up liquid spill into absorbent material. Absorb spilled material with sand or earth. Shovel or sweep up and put in a closed container for disposal. Clean contaminated surfaces with an excess of water.  
Other information : Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.  
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Keep at temperatures above freezing. Allowing freezing conditions may degrade product.

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

Incompatible products	: Oxidizing agent. Strong acids. Strong bases.
Information on mixed storage	: Store away from foodstuffs.
Storage area	: Store away from heat. Store in a well-ventilated place.
Special rules on packaging	: Keep only in original container. Store in a closed container.

### 7.3. Specific end use(s)

Refer to Section 1.2 - Relevant identified uses.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 National occupational exposure and biological limit values

Aluminium Oxide (1344-28-1)	
<b>Austria - Occupational Exposure Limits</b>	
MAK (OEL TWA)	5 mg/m <sup>3</sup> (respirable fraction, smoke)
MAK (OEL STEL)	10 mg/m <sup>3</sup> (respirable fraction, smoke)
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Aluminium (métal et composés insolubles, fraction alvéolaire) # Aluminium (metaal en onoplosbare verbindingen, inadembare fractie)
OEL TWA	1 mg/m <sup>3</sup>
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
<b>Croatia - Occupational Exposure Limits</b>	
GVI (OEL TWA) [1]	10 mg/m <sup>3</sup> (total dust, inhalable particles) 4 mg/m <sup>3</sup> (respirable dust)
<b>Denmark - Occupational Exposure Limits</b>	
OEL TWA [1]	5 mg/m <sup>3</sup> (total) 2 mg/m <sup>3</sup> (respirable)
<b>Estonia - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup> (total dust) 4 mg/m <sup>3</sup> (respirable dust)
<b>France - Occupational Exposure Limits</b>	
Local name	Aluminium (Trioxyde de di-)
VME (OEL TWA)	10 mg/m <sup>3</sup>
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
<b>Greece - Occupational Exposure Limits</b>	
Local name	Αλουμίνα, α-
OEL TWA	10 mg/m <sup>3</sup> αναπν. 5 mg/m <sup>3</sup> εισπν.
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
<b>Hungary - Occupational Exposure Limits</b>	
AK (OEL TWA)	6 mg/m <sup>3</sup> (respirable dust)
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Aluminium oxides

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

Aluminium Oxide (1344-28-1)	
OEL TWA [1]	10 mg/m <sup>3</sup> total inhalable dust 4 mg/m <sup>3</sup> respirable dust
Regulatory reference	Chemical Agents Code of Practice 2021
Latvia - Occupational Exposure Limits	
OEL TWA	6 mg/m <sup>3</sup> (disintegration aerosol)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m <sup>3</sup> (inhalable fraction) 2 mg/m <sup>3</sup> (respirable fraction)
Poland - Occupational Exposure Limits	
Local name	Tritlenek glinu
NDS (OEL TWA)	2.5 mg/m <sup>3</sup> w przeliczeniu na Al: frakcja wdychalna 1.2 mg/m <sup>3</sup> w przeliczeniu na Al: frakcja respirabilna
Remark	Frakcja wdychalna – frakcja aerozolu wnikająca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia. Frakcja respirabilna – frakcja aerozolu wnikająca do dróg oddechowych, która stwarza zagrożenie dla zdrowia po zdeponowaniu w obszarze wymiany gazowej.
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
OEL TWA	10 mg/m <sup>3</sup> (particulate matter containing no Asbestos and <1% Crystalline silica)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen
Romania - Occupational Exposure Limits	
OEL TWA	2 mg/m <sup>3</sup> (aerosols) 3 mg/m <sup>3</sup> (dust (Aluminium and Aluminium oxides) 1 mg/m <sup>3</sup> (fume (Aluminium and Aluminium oxides)
OEL STEL	5 mg/m <sup>3</sup> (aerosols) 10 mg/m <sup>3</sup> (dust (Aluminium and Aluminium oxides) 3 mg/m <sup>3</sup> (fume (Aluminium and Aluminium oxides)
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	4 mg/m <sup>3</sup> (inhalable dust)
Spain - Occupational Exposure Limits	
Local name	Óxido de aluminio (Corindón)
VLA-ED (OEL TWA) [1]	10 mg/m <sup>3</sup>
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	5 mg/m <sup>3</sup> (total dust) 2 mg/m <sup>3</sup> (respirable fraction)
United Kingdom - Occupational Exposure Limits	
Local name	Aluminium oxides
WEL TWA (OEL TWA) [1]	10 mg/m <sup>3</sup> inhalable dust 4 mg/m <sup>3</sup> respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Norway - Occupational Exposure Limits	
Local name	Aluminiumoksid
Grønseverdi (OEL TWA) [1]	10 mg/m <sup>3</sup>

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

<b>Aluminium Oxide (1344-28-1)</b>	
Korttidsverdi (OEL STEL)	15 mg/m <sup>3</sup> (equal to the limit value for Nuisance dust)
Remark	1) Grenseverdien er fastsatt lik verdien for sjenerende støv.
Regulatory reference	FOR-2021-06-28-2248
<b>Switzerland - Occupational Exposure Limits</b>	
Local name	Aluminium oxyde / Aluminiumoxid [Korund]
MAK (OEL TWA) [1]	3 mg/m <sup>3</sup> (respirable dust, smoke)
KZGW (OEL STEL)	24 mg/m <sup>3</sup> (respirable dust, smoke)
Critical toxicity	Formel / Formal
Notation	B / B
Remark	NIOSH
Regulatory reference	www.suva.ch, 28.03.2022
<b>Switzerland - BAT</b>	
Local name	Aluminium oxyde / Aluminiumoxid
BAT	50 µg/g creatinine (0.21 µmol/mmol cr.; Paramètre biologique: Aluminium; Substrat d'examen: Urine; Moment du prélèvement: Exposition de longue durée: après plusieurs périodes de travail.) / (0.21 µmol/mmol cr.; Biologischer Parameter: Aluminium; Untersuchungsmaterial: Urin; Probennahmezeitpunkt: Bei Langzeitexposition: nach mehreren vorangegangenen Schichten.)
Regulatory reference	Ordonnance 832.30 (OPA), article 50 al. 3, www.suva.ch/valeurs-limites / Verordnung 832.30 (VUV), Art. 50 Abs. 3, www.suva.ch/grenzwerte
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	1 mg/m <sup>3</sup>
<b>5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)</b>	
<b>Austria - Occupational Exposure Limits</b>	
MAK (OEL TWA)	0.05 mg/m <sup>3</sup> (5-Chloro-2-methyl-2,3-dihydroisothiazol-3-one and 2-methyl-2,3-dihydroisothiazol-3-one mixture in ratio 3:1)
OEL chemical category	Skin sensitizer
<b>Switzerland - Occupational Exposure Limits</b>	
Local name	2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle et 2,3-dihydro-isothiazol-3-one de 2-méthyle [2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle, 2,3-Dihydro-isothiazol-3-one de 2-méthyle] / 5-Chlor-2-methyl-2,3-dihydro-isothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on [2-Methyl-2,3-dihydroisothiazol-3-on, 5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on]
MAK (OEL TWA) [1]	0.2 mg/m <sup>3</sup> (i) / (e)
KZGW (OEL STEL)	0.4 mg/m <sup>3</sup> (i) / (e)
Critical toxicity	VRS, Peau, Yeux / OAW, Haut, Auge
Notation	S, SS <sub>c</sub> / S, SS <sub>c</sub>
Regulatory reference	www.suva.ch, 28.03.2022
<b>Sodium Nitrate (7631-99-4)</b>	
<b>Czech Republic - Occupational Exposure Limits</b>	
PEL (OEL TWA)	6 mg/m <sup>3</sup> (dust)

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)	
<b>Switzerland - Occupational Exposure Limits</b>	
Local name	Distillats légers de pétrole, hydrotraités (vapeurs) / Destillate (Erdöl), mit Wasserstoff behandelte, leichte (Dampf)
MAK (OEL TWA) [1]	350 mg/m <sup>3</sup>
MAK (OEL TWA) [2]	50 ppm (vapour)
KZGW (OEL STEL)	700 mg/m <sup>3</sup>
KZGW (OEL STEL) [ppm]	100 ppm (vapour)
Critical toxicity	SNC / ZNS
Notation	SS <sub>c</sub> / SS <sub>c</sub>
Remark	OSHA
Regulatory reference	www.suva.ch, 28.03.2022
<b>Glycerine (56-81-5)</b>	
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Glycérine (brouillard) # Glycerine (nevel)
OEL TWA	10 mg/m <sup>3</sup>
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
<b>Croatia - Occupational Exposure Limits</b>	
GVI (OEL TWA) [1]	10 mg/m <sup>3</sup>
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	Glycerol, mlha
PEL (OEL TWA)	10 mg/m <sup>3</sup>
PEL (OEL TWA) [ppm]	2.6 ppm
NPK-P (OEL C)	15 mg/m <sup>3</sup>
NPK-P (OEL C) [ppm]	3.9 ppm
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
<b>Estonia - Occupational Exposure Limits</b>	
OEL TWA	10 mg/m <sup>3</sup>
<b>Finland - Occupational Exposure Limits</b>	
Local name	Glyseroli
HTP (OEL TWA) [1]	20 mg/m <sup>3</sup>
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
<b>France - Occupational Exposure Limits</b>	
Local name	Glycérine (aérosols de)
VME (OEL TWA)	10 mg/m <sup>3</sup>
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
Local name	Glycerin
AGW (OEL TWA) [1]	200 mg/m <sup>3</sup> (E)
Peak exposure limitation factor	2(I)



# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

Glycerine (56-81-5)	
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Greece - Occupational Exposure Limits	
Local name	Γλυκερίνη
OEL TWA	10 mg/m <sup>3</sup>
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Poland - Occupational Exposure Limits	
Local name	Glicerol
NDS (OEL TWA)	10 mg/m <sup>3</sup> frakcja wdychalna
Remark	Frakcja wdychalna – frakcja aerozolu wnikająca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia.
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
OEL TWA	10 mg/m <sup>3</sup> (mist)
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	11 mg/m <sup>3</sup>
Slovenia - Occupational Exposure Limits	
OEL TWA	200 mg/m <sup>3</sup> (inhalable fraction)
OEL STEL	400 mg/m <sup>3</sup> (inhalable fraction)
Spain - Occupational Exposure Limits	
Local name	Glicerina
VLA-ED (OEL TWA) [1]	10 mg/m <sup>3</sup> nieblas
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
United Kingdom - Occupational Exposure Limits	
Local name	Glycerol
WEL TWA (OEL TWA) [1]	10 mg/m <sup>3</sup> mist
WEL STEL (OEL STEL)	30 mg/m <sup>3</sup> (calculated-mist)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Switzerland - Occupational Exposure Limits	
Local name	Glycérine / Glycerin
MAK (OEL TWA) [1]	50 mg/m <sup>3</sup> (i) / (e)
KZGW (OEL STEL)	100 mg/m <sup>3</sup> (i) / (e)
Critical toxicity	VRS / OAW
Notation	SS <sub>c</sub> / SS <sub>c</sub>
Regulatory reference	www.suva.ch, 28.03.2022

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

White mineral oil (petroleum) (8042-47-5)	
<b>Belgium - Occupational Exposure Limits</b>	
OEL TWA	5 mg/m <sup>3</sup>
OEL STEL	10 mg/m <sup>3</sup>
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
Local name	Weißes Mineralöl (Erdöl)
AGW (OEL TWA) [1]	5 mg/m <sup>3</sup> (A)
Peak exposure limitation factor	4(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
<b>Netherlands - Occupational Exposure Limits</b>	
TGG-8u (OEL TWA)	5 mg/m <sup>3</sup>
<b>Switzerland - Occupational Exposure Limits</b>	
Local name	Huile de paraffine / Weissöl, pharmazeutisch
MAK (OEL TWA) [1]	5 mg/m <sup>3</sup> (i) / (e)
Critical toxicity	Poumons / Lunge
Notation	SS <sub>c</sub> / SS <sub>c</sub>
Remark	NIOSH, DFG
Regulatory reference	www.suva.ch, 28.03.2022
<b>USA - ACGIH - Occupational Exposure Limits</b>	
ACGIH OEL TWA	5 mg/m <sup>3</sup>

### 8.1.2. Recommended monitoring procedures

No additional information available

### 8.1.3. Air contaminants formed

No additional information available

### 8.1.4. DNEL and PNEC

No additional information available

### 8.1.5. Control banding

No additional information available

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

#### Appropriate engineering controls:

Ensure good ventilation of the work station.

### 8.2.2. Personal protection equipment

#### Personal protective equipment:

Wear recommended personal protective equipment.

#### Personal protective equipment symbol(s):



# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

### 8.2.2.1. Eye and face protection

**Eye protection:**

Wear security glasses which protect from splashes

### 8.2.2.2. Skin protection

**Skin and body protection:**

Wear suitable protective clothing

**Hand protection:**

Protective gloves. Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl").

### 8.2.2.3. Respiratory protection

**Respiratory protection:**

No respiratory protection needed under normal use conditions. In case of insufficient ventilation, wear suitable respiratory equipment. The fine-dust mask with exhale Valve is recommended to use when dust and mist exceed exposure limits in air, according to EN149:2001 + A1:2009 FFP2 NR standard. The respiratory mask should be worn when respiratory hazards has been identified and evaluated. Respiratory protection should be always determined on quantitative exposure assessments.

### 8.2.2.4. Thermal hazards

No additional information available

### 8.2.3. Environmental exposure controls

**Environmental exposure controls:**

Avoid release to the environment. Prevent entry into waterways, sewers, basements or confined areas.

**Other information:**

Do not eat, drink or smoke when using this product.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Appearance	: Thick liquid.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: ≈ 0 °C
Boiling point	: ≈ 100 °C
Flammability	: Not applicable
Explosive properties	: Product is not explosive.
Oxidising properties	: Non oxidizing material according to EC criteria.
Explosive limits	: Not applicable
Lower explosion limit	: Not applicable.
Upper explosion limit	: Not applicable.
Flash point	: > 93 °C
Auto-ignition temperature	: > 200 °C
Decomposition temperature	: Not available
pH	: 8 – 9
Viscosity, kinematic	: 20000 mm <sup>2</sup> /s (20°C)
Solubility	: Dispersible in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.48
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

No additional information available

#### 9.2.2. Other safety characteristics

VOC content : 162 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not Classified  
Acute toxicity (dermal) : Not Classified  
Acute toxicity (inhalation) : Not Classified

#### Aluminium Oxide (1344-28-1)

LD50 oral rat	> 15900 mg/kg bodyweight
LC50 Inhalation - Rat	> 2.3 mg/l air

#### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

LD50 oral rat	490 mg/kg bodyweight
LD50 oral	670 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight
LD50 dermal	4115 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	100 mg/l

#### 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

LD50 oral rat	66 mg/kg bodyweight
LD50 dermal rat	> 1008 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	0.17 mg/l air

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

<b>Sodium Nitrate (7631-99-4)</b>	
LD50 oral rat	≈ 3430 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	3700 mg/kg
LD50 dermal rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

<b>Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics (64742-47-8)</b>	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h

<b>Glycerine (56-81-5)</b>	
LD50 oral rat	27200 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 10 g/kg
LD50 dermal	56750 mg/kg
LC50 Inhalation - Rat	5.85 mg/l

<b>White mineral oil (petroleum) (8042-47-5)</b>	
LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rabbit	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat	> 5 mg/l

Skin corrosion/irritation : Not Classified  
pH: 8 – 9

<b>5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)</b>	
pH	3.43 Temp.: 20 °C Concentration: 10 g/L

<b>Sodium Nitrate (7631-99-4)</b>	
pH	7 Temp.: 25 °C Remarks on result: 'other:'

<b>Glycerine (56-81-5)</b>	
pH	5.5 – 8

Serious eye damage/irritation : Not Classified  
pH: 8 – 9

<b>5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)</b>	
pH	3.43 Temp.: 20 °C Concentration: 10 g/L

<b>Sodium Nitrate (7631-99-4)</b>	
pH	7 Temp.: 25 °C Remarks on result: 'other:'

<b>Glycerine (56-81-5)</b>	
pH	5.5 – 8

Respiratory or skin sensitisation : Not Classified  
Germ cell mutagenicity : Not Classified  
Carcinogenicity : Not Classified  
Reproductive toxicity : Not Classified

<b>Aluminium Oxide (1344-28-1)</b>	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

NOAEL (animal/female, F1)	56.6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
---------------------------	---

STOT-single exposure : Not Classified

STOT-repeated exposure : Not Classified

### Aluminium Oxide (1344-28-1)

LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0.015 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
---	--

NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
--	---

### 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

LOAEL (dermal, rat/rabbit, 90 days)	0.525 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)
-------------------------------------	--

### Sodium Nitrate (7631-99-4)

NOAEL (oral, rat, 90 days)	≥ 1500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
----------------------------	--

### White mineral oil (petroleum) (8042-47-5)

NOAEL (oral, rat, 90 days)	≥ 1200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
----------------------------	--

Aspiration hazard : Not Classified

## FARECLA G3 PRO SCRATCH REMOVER LIQUID

Viscosity, kinematic	20000 mm <sup>2</sup> /s (20°C)
----------------------	---------------------------------

### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

Hydrocarbon	Yes
-------------	-----

### White mineral oil (petroleum) (8042-47-5)

Viscosity, kinematic	3 – 20.5 mm <sup>2</sup> /s
----------------------	-----------------------------

## 11.2. Information on other hazards

No additional information available

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not Classified

Hazardous to the aquatic environment, long-term (chronic) : Not Classified

Not rapidly degradable

### Aluminium Oxide (1344-28-1)

LC50 - Fish [1]	1.16 mg/l
-----------------	-----------

EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
----------------------	---

EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
----------------------	--

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

<b>1,2-benzisothiazol-3(2H)-one (2634-33-5)</b>	
LC50 - Fish [1]	2.18 mg/l
LC50 - Fish [2]	2.15 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	2.94 mg/l
EC50 - Crustacea [2]	2.9 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	2.94 mg/l waterflea
EC50 - Other aquatic organisms [2]	0.11 mg/l
ErC50 algae	150 µg/l

<b>5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)</b>	
LC50 - Fish [1]	0.19 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	0.28 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	0.16 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	0.0052 mg/l (Skeletonema costatum) (OECD 201)
EC50 72h - Algae [1]	0.048 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC (chronic)	0.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.098 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '28 d'
NOEC chronic crustacea	0.004 mg/l 21 d (Daphnia) (OECD 211)
NOEC chronic algae	0.0012 mg/l 72 h (Pseudokirchneriella subcapitata) (OECD 201)

<b>Sodium Nitrate (7631-99-4)</b>	
LC50 - Fish [1]	1559 mg/l Test organisms (species): other:
LC50 - Fish [2]	1354 mg/l Test organisms (species): other:
EC50 - Crustacea [1]	8609 mg/l

<b>Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics (64742-47-8)</b>	
LC50 - Fish [1]	2.2 mg/l

<b>Glycerine (56-81-5)</b>	
LC50 - Fish [1]	54000 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 10000 mg/l

<b>White mineral oil (petroleum) (8042-47-5)</b>	
LC50 - Fish [1]	> 100 mg/l

## 12.2. Persistence and degradability

<b>FARECLA G3 PRO SCRATCH REMOVER LIQUID</b>	
Persistence and degradability	Inherently biodegradable.

<b>Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics (64742-47-8)</b>	
Persistence and degradability	No persistence data available for this product.

<b>Glycerine (56-81-5)</b>	
Biochemical oxygen demand (BOD)	0.87 g O <sub>2</sub> /g substance

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

### Glycerine (56-81-5)

Chemical oxygen demand (COD)	1.16 g O <sub>2</sub> /g substance
ThOD	1.217 g O <sub>2</sub> /g substance

### 12.3. Bioaccumulative potential

#### FARECLA G3 PRO SCRATCH REMOVER LIQUID

Bioaccumulative potential	No indication of bio-accumulation potential.
---------------------------	--

#### Aluminium Oxide (1344-28-1)

Bioaccumulative potential	No bioaccumulation data available.
---------------------------	------------------------------------

#### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

BCF - Fish [1]	6.62
Partition coefficient n-octanol/water (Log Pow)	-0.9 – 0.99

#### 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

BCF - Fish [1]	41 – 54
Bioconcentration factor (BCF REACH)	3.6 (calculated) S 1177
Partition coefficient n-octanol/water (Log Pow)	0.75

#### Sodium Nitrate (7631-99-4)

Partition coefficient n-octanol/water (Log Pow)	-3.8
---	------

#### Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

Partition coefficient n-octanol/water (Log Kow)	6 – 8.2
---	---------

### Glycerine (56-81-5)

BCF - Fish [1]	(no bioaccumulation)
Partition coefficient n-octanol/water (Log Pow)	-1.75
Partition coefficient n-octanol/water (Log Kow)	-1.76

#### White mineral oil (petroleum) (8042-47-5)

BCF - Other aquatic organisms [1]	1216 l/kg
Partition coefficient n-octanol/water (Log Pow)	5.18

### 12.4. Mobility in soil

#### FARECLA G3 PRO SCRATCH REMOVER LIQUID

Ecology - soil	Semi-solid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile.
----------------	---

#### 1,2-benzisothiazol-3(2H)-one (2634-33-5)

Surface tension	72.6 mN/m
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.97

#### 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.81 – 1
--	----------



# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

### Glycerine (56-81-5)

Surface tension 63.4 mN/m

Organic Carbon Normalized Adsorption Coefficient (Log Koc) 0

### White mineral oil (petroleum) (8042-47-5)

Organic Carbon Normalized Adsorption Coefficient (Log Koc) 2.64

## 12.5. Results of PBT and vPvB assessment

### FARECLA G3 PRO SCRATCH REMOVER LIQUID

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

## 12.6. Endocrine disrupting properties

No additional information available

## 12.7. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
European List of Waste (LoW) code : 08 04 12 - adhesive and sealant sludges other than those mentioned in 08 04 11

## SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
<b>14.1. UN number or ID number</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.2. UN proper shipping name</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.3. Transport hazard class(es)</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.4. Packing group</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
<b>14.5. Environmental hazards</b>				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

### 14.6. Special precautions for user

#### Overland transport

Not regulated

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

### Transport by sea

Not regulated

### Air transport

Not regulated

### Inland waterway transport

Not regulated

### Rail transport

Not regulated

## 14.7. Maritime transport in bulk according to IMO instruments

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. New Zealand Regulation

This mixture is not classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017.

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

### Abbreviations and acronyms:

ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
IARC	International Agency for Research on Cancer
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
SDS	Safety Data Sheet

### Full text of H- and EUH-statements:

Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Asp. Tox. 1	Aspiration hazard, Category 1

# FARECLA G3 PRO SCRATCH REMOVER LIQUID

## Safety Data Sheet (New Zealand)

### Full text of H- and EUH-statements:

EUH208	Contains 1,2-benzisothiazol-3(2H)-one(2634-33-5), 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone(55965-84-9). May produce an allergic reaction.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H272	May intensify fire; oxidiser.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Ox. Sol. 3	Oxidising Solids, Category 3
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A

### Safety Data Sheet (SDS), EU

While Farecla Products Ltd. believes that the data and information contained herein are factual and the opinions are those of qualified experts, they are not to be taken as a warranty or representation for which Farecla assumes any legal responsibility. They are offered solely for the consideration, investigation, data and information in accordance with applicable laws and regulations.