



FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

Issue date: 25/9/2024 Revision date: 25/9/2024 Supersedes version of: 10/16/2019 Version: 1.7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: FARECLA G360 SUPER FAST COMPOUND
Product code	: FAG360SK
Type of product	: Polishes and wax blends
Product group	: Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public	
Main use category	: Consumer use, Professional use
Use of the substance/mixture	: Abrasive polishing compound
Function or use category	: Cleaning/washing agents and additives

1.2.2. Uses advised against

Restrictions on use	: This material should not be used for any other purpose than the identified uses without expert advice. Improper use may cause potential health, safety and environmental risks, Polishes and wax blends
---------------------	---

1.3. Details of the supplier of the safety data sheet

Manufacturer

Farecla Products Limited
Broadmeads
Ware, SG12 9HS – Hertfordshire
UK
T +44 (0)19 2046 5041 (8:30-16:30 Monday to Friday)
F +44 (0)19 2046 6557
technical@farecla.com - www.farecla.com

Supplier

Wyatt Machine Tools (Rupes) NZ Limited
388 Church Street
Penrose
Auckland
New Zealand
T (09) 525 1000, F (09) 525 1009

1.4. Emergency telephone number

Emergency number	: 0800 992 881 (0800WYATT1)
------------------	-----------------------------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not Classified

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Precautionary statements (CLP)	: P102 - Keep out of reach of children.
EUH-statements	: EUH210 - Safety data sheet available on request. EUH208 - Contains 1,2-benzisothiazol-3(2H)-one(2634-33-5), 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone(55965-84-9). May produce an allergic reaction.

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

2.3. Other hazards

Other hazards which do not result in classification : If in eyes: this material may cause mechanical irritation. Long term inhalation of product dust may be harmful.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Aluminium Oxide (1344-28-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
1,2-benzisothiazol-3(2H)-one (2634-33-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Sodium Nitrate (7631-99-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Glycerol (56-81-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
White mineral oil (petroleum)(8042-47-5)	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Aluminium Oxide	CAS-No.: 1344-28-1 EC-No.: 215-691-6 REACH-no: 01-2119529248-35	30 - 50	Not Classified
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-47-8 EC-No.: 926-141-6 REACH-no: 01-2119456620-43	10 - 30	Asp. Tox. 1, H304
White mineral oil (petroleum)	CAS-No.: 8042-47-5 EC-No.: 232-455-8 REACH-no: 2119487078-27	1 - 10	Not Classified
Glycerol	CAS-No.: 56-81-5 EC-No.: 200-289-5 REACH-no: 01-2119471987-18	1 - 10	Not Classified

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS-No.: 1174522-19-0 EC-No.: 919-029-3 REACH-no: 01-2119457735-29	1 - 10	Asp. Tox. 1, H304
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	< 0.05	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	< 0.015	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Sodium Nitrate	CAS-No.: 7631-99-4 EC-No.: 231-554-3 REACH-no: 01-2119488221-41	< 0.003	Ox. Sol. 3, H272 Eye Irrit. 2, H319
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	CAS-No.: 55965-84-9 EC-No.: 911-418-6 EC Index-No.: 613-167-00-5 REACH-no: 01-2120764691-48	< 0.0015	Acute Tox. 3 (Oral), H301 Acute Tox. 2 (Dermal), H310 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)

Specific concentration limits:

Name	Product identifier	Specific concentration limits
White mineral oil (petroleum)	CAS-No.: 8042-47-5 EC-No.: 232-455-8 REACH-no: 2119487078-27	(0 ≤C < 100) Asp. Tox. 1, H304
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	(0.05 ≤C ≤ 100) Skin Sens. 1, H317
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	CAS-No.: 55965-84-9 EC-No.: 911-418-6 EC Index-No.: 613-167-00-5 REACH-no: 01-2120764691-48	(0.0015 ≤C ≤ 100) Skin Sens. 1A, H317 (0.06 ≤C < 0.6) Skin Irrit. 2, H315 (0.06 ≤C < 0.6) Eye Irrit. 2, H319 (0.6 ≤C ≤ 100) Skin Corr. 1C, H314 (0.6 ≤C ≤ 100) Eye Dam. 1, H318

Comments

: Contains amongst other ingredients:
>30% aluminium oxide; 15-30% aliphatic hydrocarbons; <5% non-ionic surfactants, polycarboxylates, fragrance, methylchlorisothiazolinone, methylisothiazolinone, benzisothiazolinone. Contains fragrance allergen: 0.015% benzyl benzoate. For more ingredient information visit www.farecla.com.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general

: IF exposed or concerned: Get medical advice/attention.

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Take off contaminated clothing. Wash skin with plenty of water. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth out with water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Inhalation may cause irritation (cough, short breathing, difficulty in breathing).
Symptoms/effects after skin contact	: Prolonged or repeated contact may cause skin to become dry. Itching.
Symptoms/effects after eye contact	: May cause eye irritation. redness, itching, tears.
Symptoms/effects after ingestion	: May cause irritation to the digestive tract. Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not scatter spilled material with high-pressure water streams.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: No fire hazard.
Explosion hazard	: No direct explosion hazard. Product is not explosive.
Reactivity in case of fire	: Fire could produce a combination of irritating and toxic gases.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon monoxide. Carbon dioxide. Nitrogen oxides.

5.3. Advice for firefighters

Precautionary measures fire	: Keep container closed when not in use.
Firefighting instructions	: Evacuate area. Exercise caution when fighting any chemical fire. Fight fire with normal precautions from a reasonable distance. Get the package away from the fire if this can be done without risk. In case of fire: stop leak if safe to do so.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: High temperature decomposition products are harmful by inhalation.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Stop leak if safe to do so. Evacuate area.
------------------	--

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Avoid contact with eyes. Keep upwind. Evacuate area.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel. Stop leak if safe to do so. Cover spill with non combustible material, e.g.: sand/earth.

6.2. Environmental precautions

Avoid release to the environment.

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material. Absorb spilled material with sand or earth. Take up mechanically (sweeping, shovelling) and collect in suitable container for disposal. Clean contaminated surfaces with an excess of water.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Wear personal protective equipment. Avoid contact with eyes.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep cool. Keep at temperatures above freezing. Allowing freezing conditions may degrade product.
Incompatible products	: Oxidizing agent. Strong acids. Strong bases.
Incompatible materials	: Direct sunlight. Heat sources. Sources of ignition.
Information on mixed storage	: Store away from foodstuffs.
Storage area	: Store away from heat. Store in a well-ventilated place.
Special rules on packaging	: Keep only in original container. Store in a closed container.

7.3. Specific end use(s)

Refer to Section 1.2 - Relevant identified uses.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Aluminium Oxide (1344-28-1)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m ³ (respirable fraction, smoke)
MAK (OEL STEL)	10 mg/m ³ (respirable fraction, smoke)
Belgium - Occupational Exposure Limits	
Local name	Aluminium (métal et composés insolubles, fraction alvéolaire) # Aluminium (metaal en onoplosbare verbindingen, inadembare fractie)
OEL TWA	1 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	10 mg/m ³ (total dust, inhalable particles) 4 mg/m ³ (respirable dust)
Denmark - Occupational Exposure Limits	
OEL TWA [1]	5 mg/m ³ (total) 2 mg/m ³ (respirable)

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

Aluminium Oxide (1344-28-1)	
Estonia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (total dust) 4 mg/m ³ (respirable dust)
France - Occupational Exposure Limits	
Local name	Aluminium (Trioxyde de di-)
VME (OEL TWA)	10 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Greece - Occupational Exposure Limits	
Local name	Αλουμίνα, α-
OEL TWA	10 mg/m ³ αναπν. 5 mg/m ³ εισπν.
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	6 mg/m ³ (respirable dust)
Ireland - Occupational Exposure Limits	
Local name	Aluminium oxides
OEL TWA [1]	10 mg/m ³ total inhalable dust 4 mg/m ³ respirable dust
Regulatory reference	Chemical Agents Code of Practice 2021
Latvia - Occupational Exposure Limits	
OEL TWA	6 mg/m ³ (disintegration aerosol)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³ (inhalable fraction) 2 mg/m ³ (respirable fraction)
Poland - Occupational Exposure Limits	
Local name	Tritlenek glinu
NDS (OEL TWA)	2.5 mg/m ³ w przeliczeniu na Al: frakcja wdychalna 1.2 mg/m ³ w przeliczeniu na Al: frakcja respirabilna
Remark	Frakcja wdychalna – frakcja aerozolu wnikaćca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia. Frakcja respirabilna – frakcja aerozolu wnikaćca do dróg oddechowych, która stwarza zagrożenie dla zdrowia po zdeponowaniu w obszarze wymiany gazowej.
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen
Romania - Occupational Exposure Limits	
OEL TWA	2 mg/m ³ (aerosols) 3 mg/m ³ (dust (Aluminium and Aluminium oxides)) 1 mg/m ³ (fume (Aluminium and Aluminium oxides))

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

Aluminium Oxide (1344-28-1)	
OEL STEL	5 mg/m ³ (aerosols) 10 mg/m ³ (dust (Aluminium and Aluminium oxides)) 3 mg/m ³ (fume (Aluminium and Aluminium oxides))
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	4 mg/m ³ (inhalable dust)
Spain - Occupational Exposure Limits	
Local name	Óxido de aluminio (Corindón)
VLA-ED (OEL TWA) [1]	10 mg/m ³
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	5 mg/m ³ (total dust) 2 mg/m ³ (respirable fraction)
United Kingdom - Occupational Exposure Limits	
Local name	Aluminium oxides
WEL TWA (OEL TWA) [1]	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Norway - Occupational Exposure Limits	
Local name	Aluminiumoksid
Grønseverdier (OEL TWA) [1]	10 mg/m ³
Korttidsverdi (OEL STEL)	15 mg/m ³ (equal to the limit value for Nuisance dust)
Remark	1) Grønseverdier er fastsatt lik verdier for sjenerende støv.
Regulatory reference	FOR-2021-06-28-2248
Switzerland - Occupational Exposure Limits	
Local name	Aluminium oxyde / Aluminiumoxid [Korund]
MAK (OEL TWA) [1]	3 mg/m ³ (a) / (a)
KZGW (OEL STEL)	24 mg/m ³ (respirable dust, smoke)
Critical toxicity	Formel / Formal
Notation	B / B
Remark	NIOSH
Regulatory reference	www.suva.ch, 01.01.2023
Switzerland - BAT	
Local name	Aluminium oxyde / Aluminiumoxid
BAT	50 µg/g creatinine (0.21 µmol/mmol cr.; Paramètre biologique: Aluminium; Substrat d'examen: Urine; Moment du prélèvement: Exposition de longue durée: après plusieurs périodes de travail.) / (0.21 µmol/mmol cr.; Biologischer Parameter: Aluminium; Untersuchungsmaterial: Urin; Probennahmezeitpunkt: Bei Langzeitexposition: nach mehreren vorangegangenen Schichten.)
Regulatory reference	Ordonnance 832.30 (OPA), article 50 al. 3, www.suva.ch/valeurs-limites / Verordnung 832.30 (VUV), Art. 50 Abs. 3, www.suva.ch/grenzwerte
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m ³

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

Switzerland - Occupational Exposure Limits

Local name	Distillats légers de pétrole, hydrotraités (vapeurs) / Destillate (Erdöl), mit Wasserstoff behandelte, leichte (Dampf)
MAK (OEL TWA) [1]	350 mg/m ³
MAK (OEL TWA) [2]	50 ppm (vapour)
KZGW (OEL STEL)	700 mg/m ³
KZGW (OEL STEL) [ppm]	100 ppm (vapour)
Critical toxicity	SNC / ZNS
Notation	SS _c / SS _c
Remark	OSHA
Regulatory reference	www.suva.ch, 01.01.2023

White mineral oil (petroleum) (8042-47-5)

Germany - Occupational Exposure Limits (TRGS 900)

Local name	Weißes Mineralöl (Erdöl)
AGW (OEL TWA) [1]	5 mg/m ³ (A)
Peak exposure limitation factor	4(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900

Switzerland - Occupational Exposure Limits

Local name	Huile de paraffine / Weissöl, pharmazeutisch
MAK (OEL TWA) [1]	5 mg/m ³ (i) / (e)
Critical toxicity	Poumons / Lunge
Notation	SS _c / SS _c
Remark	NIOSH, DFG
Regulatory reference	www.suva.ch, 01.01.2023

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

Austria - Occupational Exposure Limits

MAK (OEL TWA)	0.05 mg/m ³ (5-Chloro-2-methyl-2,3-dihydroisothiazol-3-one and 2-methyl-2,3-dihydroisothiazol-3-one mixture in ratio 3:1)
OEL chemical category	Skin sensitizer

Switzerland - Occupational Exposure Limits

Local name	2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle et 2,3-dihydro-isothiazol-3-one de 2-méthyle [2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle, 2,3-Dihydro-isothiazol-3-one de 2-méthyle] / 5-Chlor-2-methyl-2,3-dihydro-isothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on [2-Methyl-2,3-dihydroisothiazol-3-on, 5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on]
MAK (OEL TWA) [1]	0.2 mg/m ³ (i) / (e)
KZGW (OEL STEL)	0.4 mg/m ³ (i) / (e)
Critical toxicity	VRS, Peau, Yeux / OAW, Haut, Auge

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	
Notation	S, SS _C / S, SS _C
Regulatory reference	www.suva.ch, 01.01.2023
Sodium Nitrate (7631-99-4)	
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	6 mg/m ³ (dust)
Glycerol (56-81-5)	
Belgium - Occupational Exposure Limits	
Local name	Glycérine (brouillard) # Glycerine (nevel)
OEL TWA	10 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	10 mg/m ³
Czech Republic - Occupational Exposure Limits	
Local name	Glycerol, mlha
PEL (OEL TWA)	10 mg/m ³
PEL (OEL TWA) [ppm]	2.6 ppm
NPK-P (OEL C)	15 mg/m ³
NPK-P (OEL C) [ppm]	3.9 ppm
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Estonia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Finland - Occupational Exposure Limits	
Local name	Glyseroli
HTP (OEL TWA) [1]	20 mg/m ³
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	Glycérine (aérosols de)
VME (OEL TWA)	10 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Glycerin
AGW (OEL TWA) [1]	200 mg/m ³ (E)
Peak exposure limitation factor	2(I)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

Glycerol (56-81-5)	
Greece - Occupational Exposure Limits	
Local name	Γλυκερίνη
OEL TWA	10 mg/m ³
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Poland - Occupational Exposure Limits	
Local name	Glicerol
NDS (OEL TWA)	10 mg/m ³ frakcja wdychalna
Remark	Frakcja wdychalna – frakcja aerozolu wnikająca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia.
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (mist)
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	11 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	200 mg/m ³ (inhalable fraction)
OEL STEL	400 mg/m ³ (inhalable fraction)
Spain - Occupational Exposure Limits	
Local name	Glicerina
VLA-ED (OEL TWA) [1]	10 mg/m ³ nieblas
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2023. INSHT
United Kingdom - Occupational Exposure Limits	
Local name	Glycerol
WEL TWA (OEL TWA) [1]	10 mg/m ³ mist
WEL STEL (OEL STEL)	30 mg/m ³ (calculated-mist)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Switzerland - Occupational Exposure Limits	
Local name	Glycérine / Glycerin
MAK (OEL TWA) [1]	50 mg/m ³ (i) / (e)
KZGW (OEL STEL)	100 mg/m ³ (i) / (e)
Critical toxicity	VRS / OAW
Notation	SS _c / SS _c
Regulatory reference	www.suva.ch, 01.01.2023

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

8.2.2.1. Eye and face protection

Eye protection:

Splash goggles

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl").

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. The fine-dust mask with exhale Valve is recommended to use when dust and mist exceed exposure limits in air, according to EN149:2001 + A1:2009 FFP2 NR standard. The respiratory mask should be worn when respiratory hazards has been identified and evaluated. Respiratory protection should be always determined on quantitative exposure assessments.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

Hygiene measures. Personal protective equipment.

Other information:

Do not eat, drink or smoke when using this product. Provide readily accessible eye wash stations and safety showers.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: White.
Appearance	: Thick liquid.
Odour	: pleasant.
Odour threshold	: Not available
Melting point	: < 0 °C
Freezing point	: Not available
Boiling point	: > 100 °C
Flammability	: Not applicable
Explosive properties	: Product is not explosive.
Oxidising properties	: Non oxidizing material according to EC criteria.
Explosive limits	: Not available
Lower explosion limit	: Not applicable.

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

Upper explosion limit	: Not applicable.
Flash point	: > 93 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 9 – 10
Viscosity, kinematic	: 20000 mm ² /s (20°C)
Viscosity, dynamic	: 20000 cP Brookfield Viscosity
Solubility	: Dispersible in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.27
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 210.5 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Not Classified
Acute toxicity (dermal)	: Not Classified
Acute toxicity (inhalation)	: Not Classified

Aluminium Oxide (1344-28-1)

LD50 oral rat	> 10000 mg/kg Source: ECHA
LC50 Inhalation - Rat	> 2.3 mg/l air
LC50 Inhalation - Rat (Dust/Mist)	> 2.3 mg/l Source: ECHA

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-19-0)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5266 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
White mineral oil (petroleum) (8042-47-5)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LD50 oral rat	490 mg/kg bodyweight
LD50 oral	670 mg/kg
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal	4115 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	100 mg/l
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	
LD50 oral rat	66 mg/kg bodyweight
LD50 dermal rat	> 1008 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	0.17 mg/l air
Sodium Nitrate (7631-99-4)	
LD50 oral rat	≈ 3430 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	3700 mg/kg
LD50 dermal rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
Glycerol (56-81-5)	
LD50 oral rat	27200 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 10 g/kg
LD50 dermal	56750 mg/kg
LC50 Inhalation - Rat	5.85 mg/l
Benzyl benzoate (120-51-4)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other:

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

Benzyl benzoate (120-51-4)

LD50 dermal rabbit	4000 mg/kg
Skin corrosion/irritation	: Not Classified pH: 9 – 10

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

pH	3.43 Temp.: 20 °C Concentration: 10 g/L
----	---

Sodium Nitrate (7631-99-4)

pH	7 Temp.: 25 °C Remarks on result: 'other:'
----	--

Glycerol (56-81-5)

pH	5.5 – 8
----	---------

Serious eye damage/irritation	: Not Classified pH: 9 – 10
-------------------------------	--------------------------------

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

pH	3.43 Temp.: 20 °C Concentration: 10 g/L
----	---

Sodium Nitrate (7631-99-4)

pH	7 Temp.: 25 °C Remarks on result: 'other:'
----	--

Glycerol (56-81-5)

pH	5.5 – 8
----	---------

Respiratory or skin sensitisation	: Not Classified
Germ cell mutagenicity	: Not Classified
Carcinogenicity	: Not Classified
Reproductive toxicity	: Not Classified

Aluminium Oxide (1344-28-1)

NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
---------------------------	--

Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-19-0)

NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 (One-Generation Reproduction Toxicity Study)
---------------------------	---

NOAEL (animal/female, F0/P)	≥ 1500 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 415 (One-Generation Reproduction Toxicity Study)
-----------------------------	---

NOAEL (animal/female, F1)	≥ 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
---------------------------	---

1,2-benzisothiazol-3(2H)-one (2634-33-5)

NOAEL (animal/female, F1)	56.6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
---------------------------	---

STOT-single exposure	: Not Classified
STOT-repeated exposure	: Not Classified

Aluminium Oxide (1344-28-1)

LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0.015 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
---	--

NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
--	---

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-19-0)	
NOAEL (oral, rat, 90 days)	≥ 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
NOAEC (inhalation, rat, vapour, 90 days)	> 10.4 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)

White mineral oil (petroleum) (8042-47-5)	
NOAEL (oral, rat, 90 days)	≥ 1200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	
LOAEL (dermal, rat/rabbit, 90 days)	0.525 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)

Sodium Nitrate (7631-99-4)	
NOAEL (oral, rat, 90 days)	≥ 1500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

Benzyl benzoate (120-51-4)	
NOAEL (dermal, rat/rabbit, 90 days)	781 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Aspiration hazard : Not Classified

FARECLA G360 SUPER FAST COMPOUND	
Viscosity, kinematic	20000 mm ² /s (20°C)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)	
Hydrocarbon	Yes

Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-19-0)	
Viscosity, kinematic	3.3 – 20 mm ² /s (20°C)

White mineral oil (petroleum) (8042-47-5)	
Viscosity, kinematic	2 mm ² /s @ 40°C
Hydrocarbon	Yes

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not Classified
Hazardous to the aquatic environment, long-term (chronic)	: Not Classified
Not rapidly degradable	

Aluminium Oxide (1344-28-1)	
LC50 - Fish [1]	0.078 – 0.108 mg/l Source: ECHA

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

Aluminium Oxide (1344-28-1)	
EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 96h - Algae [1]	> 0.024 mg/l Source: ECHA
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)	
LC50 - Fish [1]	2.2 mg/l
1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LC50 - Fish [1]	≈ 16.7 mg/l Test organisms (species): Cyprinodon variegatus
LC50 - Fish [2]	2.15 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	2.94 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	2.9 mg/l Test organisms (species): Daphnia magna
EC50 - Other aquatic organisms [1]	2.94 mg/l waterflea
EC50 - Other aquatic organisms [2]	0.11 mg/l
ErC50 algae	150 µg/l
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	
LC50 - Fish [1]	0.19 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	0.28 mg/l Test organisms (species): Lepomis macrochirus
EC50 - Crustacea [1]	0.16 mg/l Test organisms (species): Daphnia magna
EC50 - Crustacea [2]	0.0052 mg/l (Skeletonema costatum) (OECD 201)
EC50 72h - Algae [1]	0.048 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC (chronic)	0.1 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	0.098 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '28 d'
NOEC chronic crustacea	0.004 mg/l 21 d (Daphnia) (OECD 211)
NOEC chronic algae	0.0012 mg/l 72 h (Pseudokirchneriella subcapitata) (OECD 201)
Sodium Nitrate (7631-99-4)	
LC50 - Fish [1]	1559 mg/l Test organisms (species): other:
LC50 - Fish [2]	1354 mg/l Test organisms (species): other:
EC50 - Crustacea [1]	8609 mg/l
Glycerol (56-81-5)	
LC50 - Fish [1]	54000 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
EC50 - Crustacea [1]	> 10000 mg/l
Benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)
EC50 - Crustacea [1]	3.09 mg/l Test organisms (species): Daphnia magna

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

12.2. Persistence and degradability

FARECLA G360 SUPER FAST COMPOUND

Persistence and degradability	Inherently biodegradable.
-------------------------------	---------------------------

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

Persistence and degradability	No persistence data available for this product.
-------------------------------	---

Glycerol (56-81-5)

Biochemical oxygen demand (BOD)	0.87 g O ₂ /g substance
---------------------------------	------------------------------------

Chemical oxygen demand (COD)	1.16 g O ₂ /g substance
------------------------------	------------------------------------

ThOD	1.217 g O ₂ /g substance
------	-------------------------------------

12.3. Bioaccumulative potential

FARECLA G360 SUPER FAST COMPOUND

Bioaccumulative potential	No indication of bio-accumulation potential.
---------------------------	--

Aluminium Oxide (1344-28-1)

Bioaccumulative potential	No bioaccumulation data available.
---------------------------	------------------------------------

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

Partition coefficient n-octanol/water (Log Kow)	6 – 8.2
---	---------

1,2-benzisothiazol-3(2H)-one (2634-33-5)

BCF - Fish [1]	6.62
----------------	------

Partition coefficient n-octanol/water (Log Pow)	-0.9 – 0.99
---	-------------

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

BCF - Fish [1]	41 – 54
----------------	---------

Bioconcentration factor (BCF REACH)	3.6 (calculated) S 1177
-------------------------------------	-------------------------

Partition coefficient n-octanol/water (Log Pow)	0.75
---	------

Sodium Nitrate (7631-99-4)

Partition coefficient n-octanol/water (Log Pow)	-3.8
---	------

Glycerol (56-81-5)

BCF - Fish [1]	(no bioaccumulation)
----------------	----------------------

Partition coefficient n-octanol/water (Log Pow)	-1.75
---	-------

Partition coefficient n-octanol/water (Log Kow)	-1.76
---	-------

Benzyl benzoate (120-51-4)

Partition coefficient n-octanol/water (Log Pow)	4
---	---

12.4. Mobility in soil

FARECLA G360 SUPER FAST COMPOUND

Ecology - soil	Semi-solid under most environmental conditions. If it enters soil, it will adsorb to soil particles and will not be mobile.
----------------	---

1,2-benzisothiazol-3(2H)-one (2634-33-5)

Surface tension	72.6 mN/m
-----------------	-----------

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.97
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.81 – 1
Glycerol (56-81-5)	
Surface tension	63.4 mN/m
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0

12.5. Results of PBT and vPvB assessment

FARECLA G360 SUPER FAST COMPOUND	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Component	
Aluminium Oxide (1344-28-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
1,2-benzisothiazol-3(2H)-one (2634-33-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Sodium Nitrate (7631-99-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Glycerol (56-81-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW) code	: 08 04 12 - adhesive and sealant sludges other than those mentioned in 08 04 11
Hazardous Waste Group	: H - Organic chemicals without halogen or sulfur (eg. water-based glue, varnish or paint) or mixed organic and inorganic substances.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

ADR	IMDG	IATA	ADN	RID
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. New Zealand Regulation

This mixture is not classified hazardous according to the EPA Hazardous Substances

(Classification) Notice 2017.15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1

FARECLA G360 SUPER FAST COMPOUND

Safety Data Sheet (New Zealand)

Full text of H- and EUH-statements:	
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains 1,2-benzisothiazol-3(2H)-one(2634-33-5), 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone(55965-84-9). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H272	May intensify fire; oxidiser.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Ox. Sol. 3	Oxidising Solids, Category 3
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

While Farecla Products Ltd. believes that the data and information contained herein are factual and the opinions are those of qualified experts, they are not to be taken as a warranty or representation for which Farecla assumes any legal responsibility. They are offered solely for the consideration, investigation, data and information in accordance with applicable laws and regulations.