

1 Identification of the substance or mixture and of the supplier**Other means of identification**Trade name: **211 BODYSOFT**

Article number: W001

Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9b Fillers, putties, plasters, modelling clay

Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

Environmental release category ERC2 Formulation into mixture

Article category AC1 Vehicles

Application of the substance / the mixture Surface protection

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

Wyatt Machine Tools (Rupes) NZ Limited

Address: 388 Church Street, Penrose, Auckland

Ph (09) 525 1000; Fax (09) 525 1009

Emergency telephone number: NZ Emergency 0800 992 881 (0800WYATT1)

Emergency telephone number:

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

2 Hazards identification**Classification of the substance or mixture**

GHS02 flame

Flammable liquids Category 3

H226 Flammable liquid and vapour.



GHS08 health hazard

Reproductive toxicity Category 2

H361 Suspected of damaging fertility or the unborn child.

Specific target organ toxicity - repeated exposure Category 1
1

H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.

Trade name: 211 BODYSOFT

GHS07

Skin irritation Category 2

H315 Causes skin irritation.

Eye irritation Category 2

H319 Causes serious eye irritation.

· **Additional information:**

3.1B Flammable liquid

3.1C Flammable liquid

6.3A Substances that are irritating to the skin

8.3A Substances that are corrosive to ocular tissue

6.4A Substances that are irritating to the eye

6.9A (Repeated exposure)-Substances that are toxic to human target organs or systems

6.8B Substances that are suspected human reproductive or developmental toxicants

· **Label elements**

· GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



GHS02



GHS07



GHS08

· Signal word Danger

· Hazard-determining components of labelling:

styrene

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

· Results of PBT and vPvB assessment

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/Information on ingredients· **Chemical characterisation: Mixtures**

· Description: Mixture of hazardous substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 471-34-1 calcium carbonate




EINECS: 207-439-9


RTECS: EV 9580000

20-<25%

Continue on page 3
NZ

Trade name: 211 BODYSOFT

CAS: 100-42-5	styrene	10-<15%
EINECS: 202-851-5	 Flammable liquids Category 3, H226	
Index number: 601-026-00-0	 Reproductive toxicity Category 2, H361; Specific target organ toxicity - repeated exposure Category 1, H372	
RTECS: WL 3675000	 Skin irritation Category 2, H315; Eye irritation Category 2, H319	

CAS: 13463-67-7	titanium dioxide	0.99%
EINECS: 236-675-5	 Carcinogenicity – Category 2, H351	
Index number: 022-006-00-2		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures**Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
No further relevant information available.

5 Fire fighting measures**Extinguishing media**

- Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Advice for firefighters

- Firefighters should always use protective equipment and breathing apparatus when handling fire coming from these products
- Special protective equipment and fire fighting procedures: Mouth respiratory protective device.
- **Additional information**
Collect contaminated fire fighting water separately. It must not enter the sewage system.
HAZ CHEM CODE: 3YE

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

- Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

Continue on page 4
NZ

Trade name: **211 BODYSOFT**

See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.
· Information about storage in one common storage facility: Not required.
· Further information about storage conditions: Keep container tightly sealed.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Control parameters**

· Ingredients with limit values that require monitoring at the workplace:

471-34-1 calcium carbonate

WES (New Zealand) Long-term value: 10 mg/m³

100-42-5 styrene

WES (New Zealand) Short-term value: 170 mg/m³, 40 ppm
Long-term value: 85 mg/m³, 20 ppm
suspected carcinogen, oto

· Regulatory information WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices
· Additional information: The lists valid during the making were used as basis.

· **Exposure controls**

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Continue on page 5

NZ

Trade name: 211 BODYSOFT

- Penetration time of glove material
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Rubber gloves
- Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

9 Physical and chemical properties**Information on basic physical and chemical properties****General Information****Appearance:**

- Form: Pasty
- Colour: Light red
- Odour: Weak, characteristic
- Odour threshold: Not determined.
- pH-value: Mixture is non-soluble (in water).
- Change in condition
- Melting point/freezing point: Undetermined.
- Initial boiling point and boiling range: 145.2 °C
- Flash point: 23 - 60 °C
- Flammability: Flammable.
- Autoignition temperature: 480 °C
- Decomposition temperature: Not determined.
- Ignition temperature: Product is not selfigniting.
- Explosive properties: Risk of explosion by shock, friction, fire or other sources of ignition.
- Explosion limits:
- Lower: 1.2 Vol %
- Upper: 8.9 Vol %
- Vapour pressure at 20 °C: 6 hPa
- **Vapour pressure:**
- Density at 20 °C: 1.75 g/cm³
- Relative density: Not determined.
- Vapour density: Not determined.
- Evaporation rate: Not determined.
- Solubility in / Miscibility with
water: Not miscible or difficult to mix.
- Partition coefficient: n-octanol/water: Not determined.
- Viscosity:
- Dynamic: Not determined.
- Kinematic at 20 °C: 0 mm²/s
- Solvent content:
- Organic solvents: 14.1 %
- VOC (EC) 250.0 g/l
- Solids content (volume): 85.9 %

Continue on page 6

NZ

Trade name: 211 BODYSOFT**Other information**

- Particle characteristics Not applicable.
- Physical state Liquid

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information**Information on toxicological effects**

- Acute toxicity
- LD/LC50 values relevant for classification:

471-34-1 calcium carbonate

Oral LD50 6,450 mg/kg (rat)

100-42-5 styrene

Oral LD50 5,000 mg/kg (rat)

Inhalative LC50/4 h 24 mg/l (rat)

13463-67-7 titanium dioxide

Oral LD50 >20,000 mg/kg (rat)

Dermal LD50 >10,000 mg/kg (rabbit)

Inhalative LC50/4 h >6.82 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Irritant to skin and mucous membranes.
- Serious eye damage/irritation Irritating effect.
- Respiratory or skin sensitisation Sensitising effect through inhalation is possible by prolonged exposure.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Irritant
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
Reproductive toxicity Category 2

12 Ecological information**Toxicity**

- **Aquatic toxicity:**
This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

Persistence and degradability

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

Behaviour in environmental systems:

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

Trade name: 211 BODYSOFT

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

· vPvB: Not applicable.

· **Other adverse effects** No further relevant information available.

* **13 Disposal considerations**

· **Waste treatment methods**

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**

· NZS, IMDG, IATA UN1263

· **UN proper shipping name**

· NZS UN1263 PAINT
· IMDG, IATA PAINT

· **Transport hazard class(es)**

· NZS



· Class 3 (F1) Flammable liquids.

· Label 3

· IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· **Packing group**

· NZS, IMDG, IATA III

· **Environmental hazards:**

· Marine pollutant: No

· **Special precautions for user** Warning: Flammable liquids.

· Hazard identification number (Kemler code): 30

· EMS Number: F-E, S-E

· Stowage Category A

· **Transport in bulk according to Annex II of**

Marpol and the IBC Code Not applicable.

Trade name: 211 BODYSOFT

Transport/Additional information:

- NZS
 - Limited quantities (LQ) 5L
 - Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- Transport category 3
- Tunnel restriction code D/E
- IMDG
 - Limited quantities (LQ) 5L
 - Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- IATA
- Remarks: HAZ CHEM CODE: 3YE
- **UN "Model Regulation":** UN 1263 PAINT, 3, III

15 Regulatory information

•3Y

Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

· **New Zealand Inventory of Chemicals**

14807-96-6 Talc (Mg₃H₂(SiO₃)₄)

471-34-1 calcium carbonate

100-42-5 styrene

13463-67-7 titanium dioxide

93685-90-6 Lecithins, egg yolk

141-78-6 ethyl acetate

1332-37-2 Iron oxide

9004-36-8 cellulose acetate butyrate

CAB 381-20

CAB 381-2

CAB 381-0.1

· **HSNO Approval numbers**

HSNO Approval number HSR 002662

Group standard name Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Hazard classification Refer to section 2

100-42-5 styrene: HSR001221

· **GHS label elements**

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word Danger**

· **Hazard-determining components of labelling:**
styrene

Trade name: 211 BODYSOFT

- Hazard statements
 - H226 Flammable liquid and vapour.
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H361 Suspected of damaging fertility or the unborn child.
 - H372 Causes damage to the hearing organs through prolonged or repeated exposure. Route of exposure: Inhalation.
- Precautionary statements
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
 - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 - P405 Store locked up.
 - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Reasons for alterations
- Relevant phrases
 - H226 Flammable liquid and vapour.
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H351 Suspected of causing cancer.
 - H361 Suspected of damaging fertility or the unborn child.
 - H372 Causes damage to organs through prolonged or repeated exposure.
- **Department issuing SDS:** Department of Quality Control
- **Contact:**
 - HB BODY S.A
 - Regulatory Officer
 - Ms Athina Kapourani
 - Ph: +30 2310 790000
 - email: a.kapourani@hbbody.com
- * Data compared to the previous version altered.

Trade name: 211 BODYSOFT**Annex: Exposure scenario****Short title of the exposure scenario****Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9b Fillers, putties, plasters, modelling clay**Process category**

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

Article category AC1 Vehicles**Environmental release category** ERC2 Formulation into mixture**Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.**Duration and frequency**

5 workdays/week.

Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Fluid**Concentration of the substance in the mixture** The substance is main component.**Used amount per time or activity** Smaller than 100 g per application.**Other operational conditions****Other operational conditions affecting environmental exposure** No special measures required.**Other operational conditions affecting worker exposure**

Avoid contact with eyes.

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Other operational conditions affecting consumer exposure No special measures required.**Other operational conditions affecting consumer exposure during the use of the product**

Not applicable.

Risk management measures**Worker protection****Organisational protective measures**

No special measures required.

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

No special measures required.

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

Pregnant women should strictly avoid inhalation or skin contact.

Tightly sealed goggles

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Trade name: 211 BODYSOFT

Observe consumer information and advice on safe use.

· **Environmental protection measures**

· **Water**

No special measures required.

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· **Soil** The product is only processed over the concrete collecting basin.

· **Disposal measures**

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer**

Not relevant for this Exposure Scenario.

This product is to be used by professional technicians only.

· **Guidance for downstream users**

No further relevant information available.

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.