

**1 Identification of the substance or mixture and of the supplier****Other means of identification**Trade name: **A715 ACCELERATOR**

Article number: W059

Relevant identified uses of the substance or mixture and uses advised against

Life cycle stages IS Use at industrial Sites

Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Process category PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

Environmental release category ERC2 Formulation into mixture

Article category AC1 Vehicles

Technical function Hardener

Application of the substance / the mixture

Accelerator

Surface protection

**Details of the supplier of the safety data sheet**

Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 &amp; MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

Wyatt Machine Tools (Rupes) NZ Limited

Address: 388 Church Street, Penrose, Auckland

Ph (09) 525 1000; Fax (09) 525 1009

Emergency telephone number: NZ Emergency 0800 992 881 (0800WYATT1)

Emergency telephone number:

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

**2 Hazards identification****Classification of the substance or mixture**

GHS02 flame

Flammable liquids Category 3

H226 Flammable liquid and vapour.



GHS05 corrosion

Skin corrosion Category 1B

H314 Causes severe skin burns and eye damage.

Serious eye damage Category 1

H318 Causes serious eye damage.

Continue on page 2

NZ

**Trade name: A715 ACCELERATOR**

GHS07

Specific target organ toxicity - single exposure Category 3 H336 May cause drowsiness or dizziness.

· **Additional information:**

3.1B Flammable liquid

3.1C Flammable liquid

8.3A Substances that are corrosive to ocular tissue

6.9 (Narcotic) Substances that are harmful to human target organs or systems

· **Label elements**

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



GHS02 GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

triethylenediamine

n-butyl ester

· Hazard statements

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Other hazards**

· **Results of PBT and vPvB assessment**

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

· PBT: Not applicable.

· vPvB: Not applicable.

**3 Composition/Information on ingredients**

· **Chemical characterisation: Mixtures**

· **Description:** Mixture of hazardous substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 123-86-4	n-butyl ester	80-<90%
EINECS: 204-658-1	Flammable liquids Category 3, H226	
Index number: 607-025-00-1	Specific target organ toxicity - single exposure Category 3, H336	
RTECS: AF 7350000		
CAS: 280-57-9	triethylenediamine	15-<20%
EINECS: 205-999-9	Skin corrosion Category 1B, H314; Serious eye damage Category 1, H318	
RTECS: HM 0354200	Acute oral toxicity Category 4, H302	
	Flammable liquids Category 4, H227	

Continue on page 3

NZ

**Trade name: A715 ACCELERATOR**

- Additional information: For the wording of the listed hazard phrases refer to section 16.

**4 First aid measures****Description of first aid measures**

- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- Information for doctor:
  - Most important symptoms and effects, both acute and delayed No further relevant information available.
  - Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

**5 Fire fighting measures****Extinguishing media**

- Suitable extinguishing agents:  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet

**Special hazards arising from the substance or mixture**

- During heating or in case of fire poisonous gases are produced.

**Advice for firefighters**

- Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

- Special protective equipment and fire fighting procedures: Mouth respiratory protective device.

- **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

**6 Accidental release measures****Personal precautions, protective equipment and emergency procedures**

- Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:**

- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.

- Dispose contaminated material as waste according to section 13.

- Ensure adequate ventilation.

**Reference to other sections**

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

**7 Handling and storage****Handling:**

- Precautions for safe handling  
Keep away from heat and direct sunlight.  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

- Information about fire - and explosion protection:

- Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

**Trade name: A715 ACCELERATOR**

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

· **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

**123-86-4 n-butyl ester**

WES (New Zealand) Short-term value: 950 mg/m<sup>3</sup>, 200 ppm

Long-term value: 713 mg/m<sup>3</sup>, 150 ppm

IOELV (EU) Short-term value: 723 mg/m<sup>3</sup>, 150 ppm

Long-term value: 241 mg/m<sup>3</sup>, 50 ppm

· **Regulatory information**

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices

IOELV (EU): (EU) 2019/1831

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Rubber gloves

Continue on page 5

NZ

**Trade name: A715 ACCELERATOR**

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

**9 Physical and chemical properties****Information on basic physical and chemical properties**

## · General Information

· Appearance:

· Form:

Fluid

· Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

· pH-value:

Mixture reacts violently with water.

· Change in condition

· Melting point/freezing point:

Undetermined.

· Initial boiling point and boiling range:

124-128 °C

· Flash point:

23 - 60 °C

· Flammability

Flammable.

· Autoignition temperature:

370 °C

· Decomposition temperature:

Not determined.

· Ignition temperature:

Product is not selfigniting.

· Explosive properties:

Risk of explosion by shock, friction, fire or other sources of ignition.

· Explosion limits:

· Lower:

1.2 Vol %

· Upper:

7.5 Vol %

· Vapour pressure at 20 °C:

10.7 hPa

· **Vapour pressure at 50 °C:**

55 hPa

· Density at 20 °C:

0.92641 g/cm<sup>3</sup>

· Relative density

Not determined.

· Vapour density

Not determined.

· Evaporation rate

Not determined.

· Solubility in / Miscibility with

· water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

· Dynamic:

Not determined.

· Kinematic at 20 °C:

0 mm<sup>2</sup>/s

· Solvent content:

· Organic solvents:

82.2 %

· VOC (EC)

761.0 g/l

· Solids content (volume):

17.8 %

**Other information**

· Particle characteristics

Not applicable.

· Physical state

Liquid

**10 Stability and reactivity**· **Reactivity** No further relevant information available.

Continue on page 6

NZ

**Trade name: A715 ACCELERATOR****Chemical stability**

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

**Possibility of hazardous reactions** No dangerous reactions known.

**Conditions to avoid** No further relevant information available.

**Incompatible materials:** No further relevant information available.

**Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information****Information on toxicological effects**

Acute toxicity

LD/LC50 values relevant for classification:

**ATE (Acute Toxicity Estimates)**

Oral LD50 9,524 mg/kg (rat)

**123-86-4 n-butyl ester**

Oral LD50 13,100 mg/kg (rat)

Dermal LD50 >5,000 mg/kg (rabbit)

Inhalative LC50/4 h >21 mg/l (rat)

**280-57-9 triethylenediamine**

Oral LD50 1,700 mg/kg (rat)

Primary irritant effect:

Skin corrosion/irritation Caustic effect on skin and mucous membranes.

Serious eye damage/irritation

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

Respiratory or skin sensitisation No sensitising effects known.

**Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

**12 Ecological information****Toxicity**

Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

**Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

**Behaviour in environmental systems:**

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

**Additional ecological information:**

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Continue on page 7

NZ

**Trade name: A715 ACCELERATOR****Results of PBT and vPvB assessment**

- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations****Waste treatment methods**

- Recommendation  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packaging:**

- Recommendation: Disposal must be made according to official regulations.

**14 Transport information****UN-Number**

- NZS, IMDG, IATA UN2920

**UN proper shipping name**

- NZS UN2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S.  
(triethylenediamine, n-butyl ester)
- IMDG, IATA CORROSIVE LIQUID, FLAMMABLE, N.O.S.  
(triethylenediamine, n-butyl ester)

**Transport hazard class(es)**

- NZS



- Class 8 (CF1) Corrosive substances.
- Label 8+3

- IMDG



- Class 8 Corrosive substances.
- Label 8/3

- IATA



- Class 8 Corrosive substances.
- Label 8 (3)

**Packing group**

- NZS, IMDG, IATA II

**Environmental hazards:**

- Marine pollutant: No

**Special precautions for user**

- Warning: Corrosive substances.
- Hazard identification number (Kemler code): 83
- EMS Number: F-E,S-C

**Trade name: A715 ACCELERATOR**

· Stowage Category	C
· Stowage Code	SW1 Protected from sources of heat. SW2 Clear of living quarters.
· <b>Transport in bulk according to Annex II of Marpol and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· NZS	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category	2
· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· <b>UN "Model Regulation":</b>	UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (TRIETHYLENEDIAMINE, N-BUTYL ESTER), 8 (3), II

**15 Regulatory information**

•3W

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

· New Zealand Inventory of Chemicals

All ingredients are listed.

· HSNO Approval numbers

123-86-4 n-butyl ester: HSR001091

· GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



GHS02 GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

triethylenediamine

n-butyl ester

· Hazard statements

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

Continue on page 9

NZ



**Trade name: A715 ACCELERATOR**

P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

**16 Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Reasons for alterations
- Relevant phrases
  - H226 Flammable liquid and vapour.
  - H227 Combustible liquid.
  - H302 Harmful if swallowed.
  - H314 Causes severe skin burns and eye damage.
  - H318 Causes serious eye damage.
  - H336 May cause drowsiness or dizziness.
- **Department issuing SDS:** Department of Quality Control
- **Contact:**
  - HB BODY S.A
  - Regulatory Officer
  - Ms Athina Kapourani
  - Ph: +30 2310 790000
  - email: a.kapourani@hbbody.com
- \* Data compared to the previous version altered.

**Trade name: A715 ACCELERATOR****Annex: Exposure scenario****Short title of the exposure scenario****Sector of Use**

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Product category PC9a** Coatings and paints, thinners, paint removers**Process category PROC8b** Transfer of substance or mixture (charging and discharging) at dedicated facilities**Article category AC1** Vehicles**Environmental release category ERC2** Formulation into mixture**Technical function** Hardener**Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

**Conditions of use** According to directions for use.**Duration and frequency** Frequency of use:**Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

**Physical state** Fluid**Concentration of the substance in the mixture** The substance is main component.**Used amount per time or activity** Smaller than 100 g per application.**Other operational conditions****Other operational conditions affecting environmental exposure** No special measures required.**Other operational conditions affecting worker exposure**

Avoid contact with eyes.

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

**Other operational conditions affecting consumer exposure** No special measures required.**Other operational conditions affecting consumer exposure during the use of the product**

Not applicable.

**Risk management measures****Worker protection****Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

**Technical protective measures**

Ensure that suitable extractors are available on processing machines

Provide explosion-proof electrical equipment.

**Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

Tightly sealed goggles

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

**Environmental protection measures****Water**

Generally, prior to the introduction of wastewater into wastewater treatment plants a neutralisation is required.

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

**Trade name: A715 ACCELERATOR**

- Soil The product is only processed over the concrete collecting basin.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer**  
This product is to be used by professional technicians only.  
Not relevant for this Exposure Scenario.
- **Guidance for downstream users**  
Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.