

**1 Identification of the substance or mixture and of the supplier****Product identifier**

This Safety Data Sheet has been prepared in accordance with the New Zealand Hazardous Substances and New Organisms Act 1996 (HSNO) and as amended.

**Other means of identification**

Trade name: **F980 1K FINE FILLER**

Article number: W010

Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9b Fillers, putties, plasters, modelling clay

Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

Environmental release category ERC2 Formulation into mixture

Article category AC1 Vehicles

Application of the substance / the mixture Surface protection

**Details of the supplier of the safety data sheet**

Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

Wyatt Machine Tools (Rupes) NZ Limited

Address: 388 Church Street, Penrose, Auckland

Ph (09) 525 1000; Fax (09) 525 1009

Emergency telephone number: NZ Emergency 0800 992 881 (0800WYATT1)

Emergency telephone number:

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

**2 Hazards identification****Classification of the substance or mixture**

GHS02 flame

Flammable liquids Category 3

H226 Flammable liquid and vapour.



GHS08 health hazard

Carcinogenicity – Category 2

H351 Suspected of causing cancer. Route of exposure:  
Inhalation.

Continue on page 2  
NZ

**Trade name: F980 1K FINE FILLER**

Reproductive toxicity Category 2

H361 Suspected of damaging fertility or the unborn child.

Specific target organ toxicity - repeated exposure Category 2  
H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin irritation Category 2

H315 Causes skin irritation.

Eye irritation Category 2

H319 Causes serious eye irritation.

**Additional information:**

3.1B Flammable liquid

3.1C Flammable liquid

6.9B Substances that are harmful to human target organs or systems

6.3A Substances that are irritating to the skin

8.3A Substances that are corrosive to ocular tissue

6.4A Substances that are irritating to the eye

6.8B Substances that are suspected human reproductive or developmental toxicants

**Label elements**

GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS02



GHS07



GHS08

Signal word Warning

Hazard-determining components of labelling:

titanium dioxide

dioctyl phthalate

cellulose nitrate, nitrogen content <12.6%

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Other hazards**

Results of PBT and vPvB assessment

This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).













PBT: Not applicable.

vPvB: Not applicable.

**Trade name: F980 1K FINE FILLER****3 Composition/Information on ingredients****Chemical characterisation: Mixtures**

Description: Mixture of hazardous substances listed below with nonhazardous additions.

**Dangerous components:**

CAS: 1330-20-7	xylene	≥10-<15%
Index number: 601-022-00-9	 Flammable liquids Category 3, H226  Acute dermal toxicity Category 4, H312; Acute inhalation toxicity Category 4, H332; Skin irritation Category 2, H315	
CAS: 471-34-1	calcium carbonate	10-<15%
EINECS: 207-439-9		
RTECS: EV 9580000		
CAS: 110-19-0	isobutyl acetate	5-<10%
EINECS: 203-745-1	 Flammable liquids Category 2, H225	
Index number: 607-026-00-7		
CAS: 13463-67-7	titanium dioxide	5-<10%
EINECS: 236-675-5	 Carcinogenicity – Category 2, H351	
Index number: 022-006-00-2		
CAS: 78-93-3	butanone	5-<10%
EINECS: 201-159-0	 Flammable liquids Category 2, H225	
Index number: 606-002-00-3	 Eye irritation Category 2, H319; Specific target organ toxicity - single exposure Category 3, H336	
RTECS: EL 6475000		
CAS: 123-86-4	n-butyl ester	5-<10%
EINECS: 204-658-1	 Flammable liquids Category 3, H226	
Index number: 607-025-00-1	 Specific target organ toxicity - single exposure Category 3, H336	
RTECS: AF 7350000		
CAS: 9004-70-0	cellulose nitrate, nitrogen content <12.6%	5-<10%
Index number: 603-037-01-3	 Specific target organ toxicity - repeated exposure Category 2, H373  Specific target organ toxicity - single exposure Category 3, H335	
CAS: 7397-62-8	butyl glycolate	1-<5%
EINECS: 230-991-7	Flammable liquids Category 4, H227	
CAS: 117-84-0	dioctyl phthalate	≥1-<3%
EINECS: 204-214-7	 Reproductive toxicity Category 2, H361	
RTECS: TI 1925000		
CAS: 7727-43-7	barium sulphate, natural	1-<5%
EINECS: 231-784-4		
RTECS: CR 0600000		
CAS: 78-83-1	butanol	≥1-<3%
EINECS: 201-148-0	 Flammable liquids Category 3, H226	
Index number: 603-108-00-1	 Serious eye damage Category 1, H318	
RTECS: NP 9625000	 Skin irritation Category 2, H315; Specific target organ toxicity - single exposure Category 3, H335	
	Specific target organ toxicity - single exposure Category 3, H336	

Additional information: For the wording of the listed hazard phrases refer to section 16.

**4 First aid measures****Description of first aid measures**

General information: Immediately remove any clothing soiled by the product.

After inhalation: In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.

After swallowing: If symptoms persist consult doctor.

Continue on page 4  
NZ

**Trade name: F980 1K FINE FILLER**

- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

**5 Fire fighting measures**

- **Extinguishing media**
- Suitable extinguishing agents:  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**  
Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
- Speial protective equipment and fire fighting procedures: Mouth respiratory protective device.
- **Additional information**  
Collect contaminated fire fighting water separately. It must not enter the sewage system.  
HAZ CHEM CODE: 3YE

**6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

**7 Handling and storage**

- **Handling:**
- Precautions for safe handling  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- Information about fire - and explosion protection:  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- Storage:  
Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

**Trade name: F980 1K FINE FILLER****8 Exposure controls/personal protection****Control parameters**

Ingredients with limit values that require monitoring at the workplace:

**1330-20-7 xylene**

WES (New Zealand) Long-term value: 217 mg/m<sup>3</sup>, 50 ppm  
oto, bio

IOELV (EU) Short-term value: 442 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 221 mg/m<sup>3</sup>, 50 ppm  
Skin

**471-34-1 calcium carbonate**

WES (New Zealand) Long-term value: 10 mg/m<sup>3</sup>

**110-19-0 isobutyl acetate**

WES (New Zealand) Long-term value: 713 mg/m<sup>3</sup>, 150 ppm

IOELV (EU) Short-term value: 723 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 241 mg/m<sup>3</sup>, 50 ppm

**78-93-3 butanone**

WES (New Zealand) Short-term value: 890 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 445 mg/m<sup>3</sup>, 150 ppm  
bio

IOELV (EU) Short-term value: 900 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 600 mg/m<sup>3</sup>, 200 ppm

**123-86-4 n-butyl ester**

WES (New Zealand) Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 713 mg/m<sup>3</sup>, 150 ppm

IOELV (EU) Short-term value: 723 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 241 mg/m<sup>3</sup>, 50 ppm

**7727-43-7 barium sulphate, natural**

WES (New Zealand) Long-term value: 10 mg/m<sup>3</sup>

**78-83-1 butanol**

WES (New Zealand) Long-term value: 152 mg/m<sup>3</sup>, 50 ppm

**Regulatory information**

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices

IOELV (EU): (EU) 2019/1831

Additional information: The lists valid during the making were used as basis.

**Exposure controls**

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

**Trade name: F980 1K FINE FILLER**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)**· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

· **Eye protection:**

Tightly sealed goggles

· **Body protection: Protective work clothing****9 Physical and chemical properties**· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**· **Form:**

Pasty

· **Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Mixture is non-soluble (in water).

· **Change in condition**· **Melting point/freezing point:**

Undetermined.

· **Initial boiling point and boiling range:**

79-80.5 °C

· **Flash point:**

23 - 60 °C

· **Flammability**

Flammable.

· **Autoignition temperature:**

370 °C

· **Decomposition temperature:**

Not determined.

· **Ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Risk of explosion by shock, friction, fire or other sources of ignition.  
Explosive when mixed with oxidising substances.

· **Explosion limits:**· **Lower:**

1.1 Vol %

· **Upper:**

7 Vol %

· **Vapour pressure at 20 °C:**

6.7-8.2 hPa

· **Vapour pressure:**· **Density at 20 °C:**

1.305 g/cm<sup>3</sup>

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with**· **water:**

Not miscible or difficult to mix.

· **Partition coefficient: n-octanol/water:**

Not determined.

· **Viscosity:**· **Dynamic:**

Not determined.

· **Kinematic at 20 °C:**

0 mm<sup>2</sup>/s

Continue on page 7  
NZ

**Trade name: F980 1K FINE FILLER**

· Solvent content:	
· Organic solvents:	43.3-43.4 %
· VOC (EC)	410.0 g/l
· Solids content (volume):	56.6-56.7 %
· <b>Other information</b>	
· Particle characteristics	Not applicable.
· Physical state	Liquid

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**· **Information on toxicological effects**

- Acute toxicity
- LD/LC50 values relevant for classification:

**ATE (Acute Toxicity Estimates)**

Dermal LD50 13,774-13,787 mg/kg (rabbit)

Inhalative LC50/4 h 75.8 mg/l

**1330-20-7 xylene**

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

Inhalative LC50/4 h 11 mg/l (ATE)

**471-34-1 calcium carbonate**

Oral LD50 6,450 mg/kg (rat)

**110-19-0 isobutyl acetate**

Oral LD50 13,400 mg/kg (rat)

**13463-67-7 titanium dioxide**

Oral LD50 &gt;20,000 mg/kg (rat)

Dermal LD50 &gt;10,000 mg/kg (rabbit)

Inhalative LC50/4 h &gt;6.82 mg/l (rat)

**78-93-3 butanone**

Oral LD50 3,300 mg/kg (rat)

Dermal LD50 5,000 mg/kg (rabbit)

**123-86-4 n-butyl ester**

Oral LD50 13,100 mg/kg (rat)

Dermal LD50 &gt;5,000 mg/kg (rabbit)

Inhalative LC50/4 h &gt;21 mg/l (rat)

**7397-62-8 butyl glycollate**

Oral LD50 4,595 mg/kg (rat)

**78-83-1 butanol**

Oral LD50 2,460 mg/kg (rat)

Dermal LD50 3,400 mg/kg (rabbit)

**Trade name: F980 1K FINE FILLER**

- Primary irritant effect:
- Skin corrosion/irritation Irritant to skin and mucous membranes.
- Serious eye damage/irritation Irritating effect.
- Respiratory or skin sensitisation Sensitising effect through inhalation is possible by prolonged exposure.
- Additional toxicological information:  
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:  
Irritant
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)  
Carcinogenicity – Category 2, Reproductive toxicity Category 2

**\* 12 Ecological information****· Toxicity****· Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

**· Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

**· Behaviour in environmental systems:**

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

**· Additional ecological information:****· General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**· Results of PBT and vPvB assessment**

· PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

· vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

· **Other adverse effects** No further relevant information available.

**\* 13 Disposal considerations****· Waste treatment methods****· Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**· Uncleaned packaging:**

· Recommendation: Disposal must be made according to official regulations.

**\* 14 Transport information****· UN-Number**

· NZS, IMDG, IATA

UN1263

**· UN proper shipping name**

· NZS

UN1263 PAINT RELATED MATERIAL

· IMDG, IATA

PAINT RELATED MATERIAL

Continue on page 9

NZ



**Trade name: F980 1K FINE FILLER**

**Transport hazard class(es)**

· NZS



· Class 3 (F1) Flammable liquids.  
· Label 3  
· IMDG, IATA



· Class 3 Flammable liquids.  
· Label 3

**Packing group**

· NZS, IMDG, IATA III

**Environmental hazards:**

· Marine pollutant: No

· **Special precautions for user** Warning: Flammable liquids.

· Hazard identification number (Kemler code): 30

· EMS Number: F-E,S-E

· Stowage Category A

· **Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

**Transport/Additional information:**

· NZS

· Limited quantities (LQ) 5L  
· Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

· Transport category 3  
· Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L  
· Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

· IATA

· Remarks: HAZ CHEM CODE: 3YE

· **UN "Model Regulation":** UN 1263 PAINT RELATED MATERIAL, 3, III

**15 Regulatory information**

· 3Y

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

HSNO Controls

Approved handler test certificate containers greater than 5L) or Class 3, required when present in quantities greater than 250L (when in

Location and transit Depot 500L (when in containers up to and including 5L)  
100L (closed containers greater than 5L) 250L (closed containers up to and

**Trade name: F980 1K FINE FILLER**

including 5L) 50L (open containers).

Hazardous Atmosphere Zone 100L (closed containers 25L (decanting) 5L (open occasionally) 1L (open containers in continuous use)

Fire extinguishers Two required for 250 L

Emergency response plan 100L (for HSNO 9.1A substance or 1,000L (for all other substances)

Secondary containment 100L (for HSNO 9.1A substance or 1,000L (for all other substances)

Tracking Not Required

Warning signage 100L (for HSNO 9.1A substance or 250L (for all other substances)

None of the ingredients is listed.

· **New Zealand Inventory of Chemicals**

1330-20-7 xylene

471-34-1 calcium carbonate

14807-96-6 Talc ( $Mg_3H_2(SiO_3)_4$ )

110-19-0 isobutyl acetate

13463-67-7 titanium dioxide

78-93-3 butanone

123-86-4 n-butyl ester

9004-70-0 cellulose nitrate, nitrogen content <12.6%

7397-62-8 butyl glycolate

117-84-0 dioctyl phthalate

7727-43-7 barium sulphate, natural

78-83-1 butanol

64-17-5 ethanol

67-63-0 propan-2-ol

71-36-3 butan-1-ol

93685-90-6 Lecithins, egg yolk

7664-38-2 phosphoric acid

1333-86-4 Carbon black

100-41-4 ethylbenzene

· **HSNO Approval numbers**

HSNO Approval number HSR 002662

Group standard name Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Hazard classification Refer to section 2

1330-20-7 xylene: HSR000983

110-19-0 isobutyl acetate: HSR001092

78-93-3 butanone: HSR001190

123-86-4 n-butyl ester: HSR001091

78-83-1 butanol: HSR001097

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** Warning

· **Hazard-determining components of labelling:**

titanium dioxide

dioctyl phthalate

cellulose nitrate, nitrogen content <12.6%

· **Hazard statements**

H226 Flammable liquid and vapour.

**Trade name: F980 1K FINE FILLER**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category P5c** FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials, Annex II:**

Carcinogenic hazardous material group III (dangerous).

· **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

\* **16 Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Reasons for alterations**

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H227 Combustible liquid.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing SDS:** Department of Quality Control

· **Contact:**

HB BODY S.A

Regulatory Officer

Ms Athina Kapourani

Ph: +30 2310 790000

email: a.kapourani@hbbody.com

· \* Data compared to the previous version altered.

**Trade name: F980 1K FINE FILLER****Annex: Exposure scenario****Short title of the exposure scenario****Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Product category PC9b** Fillers, putties, plasters, modelling clay**Process category**

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

**Article category AC1** Vehicles**Environmental release category ERC2** Formulation into mixture**Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

**Conditions of use** According to directions for use.**Duration and frequency** Frequency of use:**Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

**Physical state** Fluid**Concentration of the substance in the mixture** The substance is main component.**Used amount per time or activity** Smaller than 100 g per application.**Other operational conditions****Other operational conditions affecting environmental exposure**

No special measures required.

Use only on hard ground.

**Other operational conditions affecting worker exposure**

Avoid contact with eyes.

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

**Other operational conditions affecting consumer exposure** No special measures required.**Other operational conditions affecting consumer exposure during the use of the product**

Not applicable.

**Risk management measures****Worker protection****Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

**Technical protective measures**

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Use product only in enclosed systems.

**Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

Pregnant women should strictly avoid inhalation or skin contact.

Tightly sealed goggles

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Continue on page 13

NZ

**Trade name: F980 1K FINE FILLER**

- **Measures for consumer protection**  
Ensure adequate labelling.  
Observe consumer information and advice on safe use.
- **Environmental protection measures**
- **Water**  
Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.  
Do not allow to reach sewage system.
- **Soil**  
The product is only processed over the concrete collecting basin.  
Prevent contamination of soil.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer**  
This product is to be used by professional technicians only.  
Not relevant for this Exposure Scenario.
- **Guidance for downstream users**  
Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.