

# **TECHNICAL INFORMATION**

FOR PROFESSIONAL USE ONLY



# R1 REGENERATION

Capacity Article number

250 ml 300007597

## **PRODUCT DESCRIPTION**

Product intended to restore and refresh plastic surfaces. Suitable also to use on metal (chrome, brass, stainless steel, aluminium) and painted or varnished surfaces. Agent has a strong penetrating ability and thanks to it he restore lost color and luster. After drying creates flexible and resistant finishing coating.

# **PHYSICAL AND CHEMICAL PROPERTIES**

Base: alkad resinConsystence: liquid

Capacity: 250 ml.

• Specific gravity: approx. 0,875

Color: amber

• Efficiency: 18 m2/l (efficiency may vary depending on the type of surface)

Drying time: 24 h. (depending on the temperature and air humidity)

Updated 12.06.2019 r.



## **USAGE**

- Surface to be treated should be clean and dry. All layers of waxes and silicone should be removed. Plastic should be cleaned with warm water with soap, rinse thoroughlynand wait at least 12 hours to dry completely.
- It's not recommended to use on white lacquers.
- Using the clean cloth or brush apply product evenly on the surface. Recommended application temperature is 5 35°C. Do not apply on hot surface.
- Leave for 10 20 min (it's recommended to work on the surface of which can be completed within max. 20 min).
- Remove product residue with clean cloth..
- Leave until dry and then polish by dry mictofiber cloth to obtain better gloss..

## **STORAGE**

Store in close sealed container in temperature 0 - 45°C.

Do not freeze. Store away from acids. Store away from oxidizing agents. Keep away from heat.

#### **WARRANTY PERIOD**

24 months from production date.

Updated 12.06.2019 r.



**Limitation of responsability:** the information contained in the TDS is up-to-date and correct on the day the information is released.

Because TROTON can not control or predict the conditions under which a product will be used, each user should review information in the specific context of the intended use. To the maximum extent permitted by applicable law, TROTON shall not be liable for damages of any kind arising from the use or reliance on information contained in this TDS.

Given the variety of factors that can affect the use and use of the TROTON product, some of which are only within the user's knowledge and control range, it is essential that the user evaluate the TROTON product to determine if the product is fit for a particular purpose and whether the product is suitable for the user's use.

Under no circumstances shall TROTON be liable to you or any third party for any indirect, incidental, incidental, special or punitive damages, including loss of profits resulting from the use of products manufactured by TROTON and / or TROTON's services.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o. Ząbrowo, Poland